

## ORA011-PW

- Secure and Safe

6mA DC residual current protection

Anti-welding protection

- Intelligent Control

Wireless communication (Wi-Fi)

OCPP communication protocol with CMS

Smart charge or scheduled charge by App

- Flexible Option

App operation or RFID authentication or plug and play



### Specifications

Model	ORA011-PW-82
<b>Input</b>	
Power Supply	3P+N+PE
Rated Voltage	400V AC
Rated Current	16A
Frequency	50/60Hz
<b>Output</b>	
Output Voltage	400V AC
Maximum Current	16A
Rated Power	11kW
<b>User Interface</b>	
Charge Connector	Type 2 cable
Cable Length	4m
Enclosure	Plastic PC940
LED Indicator	Green/Yellow/Red
RFID Reader	Mifare ISO/IEC 14443 A
Start Mode	Plug&Play/RFID card/App
Emergency Stop	No
<b>Communication</b>	
Wi-Fi	Yes
OCPP	OCPP 1.6 Json (OCPP 2.0 optional)
<b>Safety</b>	
Energy Meter	No
RCD	6mA DC
Ingress Protection	IP65
Ingress Protection	IK10
Electrical Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection
Certification	CE
Certification Standard	EN/IEC 61851-1: 2017, EN/IEC 61851-21-2: 2018
Warranty	2 years
<b>Environment</b>	
Installation	Wall-mount/Pole-mount
Work Temperature	-30°~+50°
Work Humidity	5%~95%
Work Altitude	<2000m
<b>Package</b>	
Product Dimension	325 x 181 x 87mm (H*W*D)
Package Dimension	434 x 324 x 210mm (L*W*H)
Net Weight	3.2kg
Gross Weight	4.0kg
External Package	Carton

\*Product specifications are subject to change without further notice