

## ADL-1108HD ADL-1116HD

### Features:

- Single USB console control 8/16 HDMI interface computer and two additional USB device
- Supports USB TYPE A interface type keyboard and mouse device
- HDMI LCD Console resolution in Max:1920x1200@60Hz(1080P); HDMI standard alone KVM resolution in Max: 4K x 2K/60Hz;
- Switch the computer through the front panel buttons, keyboard hotkeys and screen menu (OSD)
- Connect to the controlled device for BIOS-level access without worrying about the risk of viruses and Trojans
- The controlled computer does not need to install any software and drivers, and the controlled computer directly recognizes KVM.
- Upgrade remote network control mode by extending IP board
- Support OSD to set user login mode and increase KVM login security requirements
- Both local and remote IP modes support high video resolution – support for 480i, 480p, 720p, 1080i and 1080p (1920 × 1200), 4K X 2K Ultra HD resolution
- Support widescreen resolution
- Support DDC communication to adapt to different graphics devices
- Auto scan function monitors all computer operations
- Support for cross-platform operations - Windows, Linux, Mac\*, and Sun\*

The computer mouse and mouse connection port is controlled by Keep Online technology to simulate the mouse and keyboard. The device is safe and stable, and the switching is fast without delay.



**SPECIFICATION:**

Function		8 Ports	16Ports	
Computer Connection		8	16	
Port Selection		OSD Menu, Front panel switches, Hot Key		
Connector	Console Connector	Monitor	1 x HDMI Female	
		Keyboard	1 x USB Type A Female	
		Mouse	1 x USB Type A Female	
	PC Connector	Monitor	8 x HDMI Female	16 x HDMI Female
		Mouse/Keyboard	8 x USB TYPE B Female	16 x USB TYPE B Female
Power Supply		1 x DC Jack		
Toggle switch	Connection Port Selection		8 x keys	16 x keys
	KVM Switch Reset		1 x Semi-embedded keys	
LED Instruction	Selected		8 x Green	16 x Green
	Online		8 x Red	16 x Red
Simulation Method	Keyboard & Mouse		USB	
Max Resolution Video		4K x 2K @ 60HZ Local		
Scan interval		3、 5、 10、 15、 20、 30、 40、 60 seconds (Default 3 Seconds)		
Operating Environment	Operating temperature		0-50°C	
	Storage temperature		-20-60°C	
	Humidity		0-80%RH, No Condensation	
Physical Properties	Housing		metal	
	Dimensions(L x W x H )		432 x 155 x 44 mm	
	Weight (kgs)		1.8KG	

\* Product Characteristics subject to change without prior notice