

ADL-C17 / ADL-C19

VGA Series 17" / 19"



Features:

- Front LCD console (keyboard, mouse, monitor 17"/19")
- IP optional (IP card could be installed inside KVM module)
- Extra prepositive USB mouse interface
- Single port length: 462.6mm

Specifications

Type		ADL-C17	ADL-C19
LCD monitor	Ratio	17" screen, 4:3	18.47" Screen, 16:9
	Video	SXGATFT-LCD	Wide AHVA TFT-LCD
	Visible square	337.920(H) x 270.336 (V)	408.96(H) x 230.04(V)
	Resolution (optimum)	1280*1024@60Hz	1920*1080 @60HZ
	Support color	16.7M (RGB 6 bit+Hi_FRC)	16.7M, True 8 bit
	Contrast	1000:1 (typ)	1000 : 1 (Typ)
	Back light	LED	LED
	Pixel pitch	0.264 X 0.297mm	213*213um
	LED MTBF	100,000 hours	100,000 hours
	Input power	12V	12V
Keyboard	Keyboard	100keys,detachable (9 different lanuages for choose)	100Keys, detachable (9 different languages for choose)
	Compaible IBM/AT	Microsoft windows9, Me/NT/2000/XP, WIN7, Server2003, Win8, Win10	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2;USB	Standard PS/2; USB
	Using life	>1,000,000 times	>1,000,000 Times
Mouse	Type	Touch screen	Touch Screen
	Port	Standard PS/2	Standard PS/2
	X/Y resolution	>1000dots/inch, (40x40/mm)	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 times	>1,000,000 Times
Dimension	407.1*445*45mm		407.1*445*45mm
Weight	6.15Kg		8.5kg





KVM module specification		
Model		ADL-V01
Computer connection	Direct connects	1
	Maximum connects	1
CPU port selection		/
Connectors	Console connector	
	PC connector	Monitor Mouse/keyboard Switch module
	Power	/
	Network port	/
Toggle switch	Connection port selection	
	KVM reset	/
	IP module reset	/
	IP module default	/
LED'S	Selected	
	On line	
	IP network	
Analog mode	Keyboard/mouse	USB, PS/2
Resolution (Max)		1920x1200@60Hz local & remote
Scan time interval		3,5,10,15,20,30,40,60s (3s by default)
Operating environment	Operating temperature	
	Storage temperature	
	Humidity	
Physical properties	Housing	
	Dimentions	
	Weight	

KVM module specification		
Model		ADL-D01
Computer connection	Direct connects	1
CPU port selection		/
Connectors	Console connector	
	PC connector	Expansion interface
		Microphone
		Audio speaker
		Mouse/Keyboard
		Monitor
		Mixed audio connector
	Power	/
Key switch	Connection port selection	
	KVM reset	
LED'S	Selected	
	On line	
Analog mode	Keyboard/mouse	USB, PS/2
Resolution (Max)		1920x1200@60Hz local & remote
Scan time interval		3,5,10,15,20,30,40,60s (3s by default)
Operating environment	Operating temperature	
	Storage temperature	
	Humidity	
Physical properties	Housing	
	Dimentions	
	Weight	