

ADL-C17 / ADL-C19

ADL-C04, ADL- C08, ADL-C16, ADL-C32

Single –rail LCD KVM console

CAT5 Series 17" / 19"



Features:

- Front LCD console (keyboard, mouse, monitor 17"/19") + KVM module design (4/8/16/32ports);
It's very flexible and convenient for combination
- IP optional (IP card could be installed inside KVM module)
- Extra prepositive USB mouse interface
- Single port length: 462.6mm; multi-ports length: 611mm

Specifications

Type		ADL-C17	ADL-C19
LCD monitor	Ratio	17" screen, 4:3	18.47" Screen, 16:9
	Video	SXGATFT-LCD	Wide AHVA TFT-LCD
	Visible square	337.920(H) x 270.336 (V)	408.96(H) x 230.04(V)
	Resolution (optimum)	1280*1024@60Hz	1920*1080 @60HZ
	Support color	16.7M (RGB 6 bit+Hi_FRC)	16.7M, True 8 bit
	Contrast	1000:1 (typ)	1000 : 1 (Typ)
	Back light	LED	LED
	Pixel pitch	0.264 X 0.297mm	213*213um
	LED MTBF	100,000 hours	100,000 hours
	Input power	12V	12V
Keyboard	Keyboard	100keys,detachable (9 different lanuages for choose)	100Keys, detachable (9 different languages for choose)
	Compaible IBM/AT	Microsoft windows9, Me/NT/2000/XP, WIN7, Server2003, Win8, Win10	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2;USB	Standard PS/2; USB
	Using life	>1,000,000 times	>1,000,000 Times
Mouse	Type	Touch screen	Touch Screen
	Port	Standard PS/2	Standard PS/2
	X/Y resolution	>1000dots/inch, (40x40/mm)	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 times	>1,000,000 Times
Dimension	407.1*445*45mm		407.1*445*45mm
Weight	6.15Kg		8.5kg

KVM module specification						
Model		ADL-C04	ADL-C08	ADL-C16	ADL-C32	
Computer connection	Direct connects	4	8	16	32	
	Maximum connects	64	128	256	512	
CPU port selection		OSD menu, front panel buttons, hot key, IP remote control (optional)				
Connectors	Console connector		DB 37PIN			
	PC connector	Monitor Mouse/keyboard Switch module	4xVGA DB15, Female blue 4x USB OR 4x PS/2	8xVGA DB15, Female blue 8x USB OR 8x PS/2	16xVGA DB15, Female blue 16x USB OR 16x PS/2	32xVGA/DVI/HDMI, 32x USB OR 32 x PS/2
		Switch module port	4xRJ45	8xRJ45	16xRJ45	32xRJ45
	Power		1x DC jack			
	Network port		1 x RJ45			
Toggle switch	Connection port selection		KVM operation panel digital keys			
	KVM reset		KVM operation panel function keys			
	IP module reset		1 x semi-embedded key			
	IP module default		1 x semi-embedded key			
LED'S	Selected		Nixie tube display			
	On line		4 x Red	8x Red	16x Red	32x Red
	IP network		1 x green, 1 x orange			
Analog mode	Keyboard/mouse		USB, PS/2			
Resolution (Max)		1920x1200@60Hz local & remote				
Scan time interval		3,5,10,15,20,30,40,60s (3s by default)				
Operating environment	Operating temperature		-10-50°C			
	Storage temperature		-20-60°C			
	Humidity		0-80%RH, no condensation			
Physical properties	Housing		metal			
	Dimentions		148.5*445*45mm			
	Weight		2.25kg	2.7Kg	3.80Kg	4.30Kg

