

ADL-C17 / ADL-C19

ADL-V01, ADL-V04, ADL-V08, ADL-V16

Single –rail LCD KVM console

VGA Series 17" / 19"



Features:

- Front LCD console (keyboard, mouse, monitor 17"/19") + KVM module design (1/4/8/16ports);
It's very flexible and convenient for combination
- IP optional (IP card could be installed inside KVM module)
- Extra prepositive USB mouse interface
- Single port length: 462.6mm; multi-ports length: 611mm

Specifications

Type		ADL-C17	ADL-C19
LCD monitor	Ratio	17" screen, 4:3	18.47" Screen, 16:9
	Video	SXGATFT-LCD	Wide AHVA TFT-LCD
	Visible square	337.920(H) x 270.336 (V)	408.96(H) x 230.04(V)
	Resolution (optimum)	1280*1024@60Hz	1920*1080 @60HZ
	Support color	16.7M (RGB 6 bit+Hi_FRC)	16.7M, True 8 bit
	Contrast	1000:1 (typ)	1000 : 1 (Typ)
	Back light	LED	LED
	Pixel pitch	0.264 X 0.297mm	213*213um
	LED MTBF	100,000 hours	100,000 hours
	Input power	12V	12V
Keyboard	Keyboard	100keys,detachable (9 different lanuages for choose)	100Keys, detachable (9 different languages for choose)
	Compaible IBM/AT	Microsoft windows9, Me/NT/2000/XP, WIN7, Server2003, Win8, Win10	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2;USB	Standard PS/2; USB
	Using life	>1,000,000 times	>1,000,000 Times
Mouse	Type	Touch screen	Touch Screen
	Port	Standard PS/2	Standard PS/2
	X/Y resolution	>1000dots/inch, (40x40/mm)	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 times	>1,000,000 Times
Dimension	407.1*445*45mm		407.1*445*45mm
Weight	6.15Kg		8.5kg

KVM module specification						
Model		ADL-V01	ADL-V04	ADL-V08	ADL-V16	
Computer connection	Direct connects	1	4	8	16	
	Maximum connects	1	64	128	256	
CPU port selection		/	OSD menu, front panel buttons, hot key, IP remote control (optional)			
Connectors	Console connector		DB 37PIN			
	PC connector	Monitor Mouse/keyboard Switch module	1xVGA DB15, USB/PS.2	4xVGA DB15, Female blue	8xVGA DB15, Female blue	16xVGA DB15, Female blue
	Power		/	1x DC jack		
	Network port		/	1 x RJ45		
Toggle switch	Connection port selection		/	KVM operation panel digital keys		
	KVM reset		KVM operation panel function keys			
	IP module reset		/	1 x semi-embedded key		
	IP module default		/	1 x semi-embedded key		
LED'S	Selected		/	Nixie tube display		
	On line		/	4 x Red	8x Red	16x Red
	IP network		/	1 x green, 1 x orange		
Analog mode	Keyboard/mouse		USB, PS/2			
Resolution (Max)		1920x1200@60Hz local & remote				
Scan time interval		3,5,10,15,20,30,40,60s (3s by default)				
Operating environment	Operating temperature		-10-50°C			
	Storage temperature		-20-60°C			
	Humidity		0-80%RH, no condensation			
Physical properties	Housing		plastic	metal		
	Dimentions		50*77*24.5mm	148.5*445*45mm		
	Weight		0.18kg	2.25kg	2.7Kg	3.80Kg

