

## EWS850-FIT



# EnGenius Fit Managed EWS850-FIT Wi-Fi 6 2x2 Outdoor Access Point

Simple • Secure • Smart



## Product Highlights

The EnGenius Fit Managed EWS850-FIT Wi-Fi 6 2x2 dual band IP67 outdoor wireless access point is a business-class device that provides secure and reliable high performance while reducing capital and operating expenses for cost-conscious small businesses. With support for the latest 802.11ax technology, this access point is capable of delivering maximum speeds of 574 Mbps (2.4 GHz frequency) and 1,200 Mbps (5 GHz frequency). Designed for peak performance in harsh climates, EnGenius Fit Wi-Fi 6 outdoor access points feature IP67-rated waterproof and dustproof enclosures ensuring they can withstand harsh outdoor environments.

Manage your network onsite or on-the-go through our **FitXpress** cloud-based mobile app or web portal. Additionally, **FitController** gives you greater control of your network using plug-n-play hardware with embedded network management software. Admins can easily view detailed analytics from a single pane of glass as well as monitor and troubleshoot issues instantly.

## Features & Benefits

- Dual concurrent 802.11ax architecture & backward-compatible with 11ac/a/b/g/n client devices; 2x2 antenna.
- Supports up to 1,200 Mbps in 5-GHz frequency band & 574 Mbps in 2.4-GHz frequency band.
- IP67-Rated weatherproof & dustproof housing withstands harsh environments.
- 2.5 GigE PoE+ compatible port for easy placement where power outlets are scarce.
- Manage your network onsite or on-the-go through our **FitXpress** cloud-based mobile app or web portal.
- **FitController** gives you greater control of your network using plug-n-play hardware with embedded network management software.
- Setup in minutes with app-based step by step instructions.
- Quick-scan device register, remote monitoring, and troubleshooting.
- Real-time system metrics, analytics, and remote configurations.
- No access point licensing or subscription fees.
- Uplink and downlink of OFDMA improves transmission to APs and client devices.
- Uplink & downlink of MU-MIMO for optimal signal & reception reliability for up to 2 devices.
- Target wake time for power-saving of client & IoT devices.
- BSS coloring for tagging packets with a "color" to differentiate between adjacent basic service sets.
- Spatial reuse identifies color sets via BSS coloring & simultaneously transmits on the same channel, reducing transmission waiting time and contention.
- GigE PoE-Compliance with 802.3af & 48V PoE input for flexible installation up-to 328 feet.
- Mesh wireless support simplifies setup, optimizes signals & self-heals.
- Four (4) (2x2) detachable 5dbi high-gain, 360° SMA-type antennas.

## Technical Specifications

### EWS850-FIT

#### Standards

IEEE 802.11b/g/n/ax on 2.4GHz

IEEE802.11a/n/ac/ax on 5GHz

#### Processor

Qualcomm® Quad-Core CPU ARM Cortex A53s @ 1.8GHz

#### Antenna

Four (4) External 5 dBi Dual-Concurrent Omni-Directional Antenna

SMA-Type

#### Physical Interface

1 x 10/100/1000/2500 BASE-T, RJ-45 Ethernet Port

#### LED Indicators

1 x Power

1 x LAN

1 x 2.4 GHz

1 x 5 GHz

#### Power Source

Power-over-Ethernet: 802.3af/at

Proprietary 48V – 54V

IEEE 802.11e Compliant Source

Active Ethernet (PoE)

#### Maximum Power Consumption

15.9W

#### Surge Protection

1KV

#### ESD Protection

Contact: 4KV

Air: 8 KV

### WIRELESS & RADIO SPECIFICATIONS

#### Operating Frequency

Dual-Radio Concurrent 2.4GHz & 5 GHz

#### Operation Modes

AP, Mesh

#### Frequency Radio

2.4GHz: 2400 MHz ~ 2482 MHz

5GHz: 5150 MHz ~ 5250 MHz, 5250 MHz ~ 5350 MHz, 5470 MHz ~ 5725 MHz, 5725MHz ~ 5850MHz

#### Transmit Power

2.4GHz: 23dBm

5GHz: 25dBm

Maximum power is limited by regulatory domain

#### (Tx Beamforming (TxBF

2x2:2

### SU-MIMO

Two (2) spatial streams SU-MIMO for 2.4GHz and two (2) spatial streams SUMIMO for 5GHz up to 1,774Mbps wireless data rate to a single 11ax wireless client device under both the 2.4G Hz and 5GHz radios.

### MU-MIMO

Two (2) spatial streams multiple (MU)-MIMO for up to 1200 Mbps wireless data rate to transmit to one (1) two streams MU-MIMO 11ax capable wireless client devices under 5GHz simultaneously.

Two (2) multiple (MU)-MIMO for up to 574 Mbps wireless data rate to transmit to one (1) two streams MU-MIMO 11ax capable wireless client devices under 2.4GHz simultaneously.

#### (Supported Data Rates (Mbps

802.11ax:

2.4 GHz: 9 to 574 (MCS0 to MCS11, NSS = 1 to 2)

5 GHz: 18 to 1200 (MCS0 to MSC11, NSS = 1 to 2)

802.11b: 1, 2, 5.5, 11

802.11a/g: 6, 9, 12, 18, 36, 48, 54

802.11n: 6.5 to 300 Mbps (MCS0 to MCS15)

802.11ac: 6.5 to 867 Mbps (MCS0 to MCS9, NSS = 1 to 2)

#### Supported Radio Technologies

802.11ax: Orthogonal Frequency Division Multiple Access (OFDMA)

802.11b: Direct-sequence spread-spectrum (DSSS)

802.11ac/a/g/n: Orthogonal Frequency Division Multiple (OFDM)

#### Channelization

802.11ax supports high efficiency (HE) –HE 20/40/80 MHz

802.11ac supports very high throughput (VHT) –VHT 20/40/80 MHz

802.11n supports high throughput (HT) –HT 20/40 MHz

802.11n supports very high throughput under the 2.4GHz radio –VHT40 MHz (256-QAM) 802.11n/ac/ax packet aggregation: A-MPDU, A-SPDU

#### Supported Modulation

802.11ax:

BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM

802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM

802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM

802.11b: BPSK, QPSK, CCK

## MANAGEMENT

### Multiple BSSID

8 SSIDs for both 2.4GHz and 5GHz radios

### VLAN Tagging

Supports 802.1q SSID-to-VLAN Tagging

Cross-band VLAN Pass Through

Management VLAN

### Spanning Tree

Supports 802.1d Spanning Tree Protocol

### (QoS (Quality of Service

Complaint With IEEE 802.11e Standard WMM

### SNMP

v1, v2c, v3

### MIB

I/II, Private MIB

### Wireless Security

WPA3-PSK (SAE)

WPA3 Enterprise

WPA2 Enterprise (AES)

WPA2 AES-PSK

OWE

Hide SSID in Beacons

MAC Address Filtering, Up to 32 MACs per SSID

Wireless STA (Client) Connected List

SSH Tunnel

Client Isolation

## ENVIRONMENT & PHYSICAL

### Temperature Range

Operating: -4°~140°F/-20°C~60°C

Storage: -40°F~176°F/-40°C~80°C

### (Humidity (non-condensing

Operating: 90% or less

Storage: 90% or less

### Waterproof & Dustproof

IP67-Rated Enclosure

## DIMENSIONS & WEIGHTS

### EWS850-FIT Device

Weight: 1.54 lbs. (0.7 kg)

Width: 4.07" (124 mm)

Length: 7.48" (190 mm)

Height" 2.07" (52.5 mm)

### Packaging

Weight: 3.96 lbs. (1.8kg)

Width: 9.21" (234 mm)

Length: 11.18" (284 mm)

Height: 5.67" (144 mm)

### Package Contents

1 – EWS850-FIT Cloud Managed Outdoor Access Point

1 - Pole-Mounting Brackets

1 - Wall-Mount Screw Set

2 - 2.4GHz 5dBi SMA Antennas

2 - 5GHz 5dBi SMA Antennas

1 - Quick Start Guide QR Code


### Certifications

FCC, CE, IC


### WARRANTY

1 Year

## Product Images



## Product Images



## EWS850-FIT Outdoor Antenna Patterns

