

ADSTS1130A Automatic Transfer Switch

- 30A max. input current
- Powered by two separately independent power sources
- Dual power supply for redundancy
- Provides seamless power switch for IT equipment
- Preferred source selection in front panel
- Highly reliability 19" rack design (1U) to fit into a diverse Working environment
- SNMP interface- Optional
- Built-in USB and RS-232 communication



Specifications

Model	ADSTS1130A
TOPOLOGY	Relay+SCR
INPUT	
Input Voltage	220/230/240 VAC
Acceptable Input Voltage Range	180 - 258 VAC
Input Frequency	50 Hz/60 Hz
Maximum Input Current	30A
OUTPUT	
Output Voltage	220/230/240 VAC
Maximum Output Current	10 A for IEC-C13 outlets 16 A for IEC-C19 outlet 30A for Grand connector
CONNECTION	
Input	2 x Grand connector
	4 x IEC-C13 1 x IEC-C19
Output	1 x Grand
Communication	USB/RS-232
TRANSFER TIME	9-12ms (Typical), 16ms max.
PHYSICAL	
Dimension, D X W X H (mm)	330 x 430 x 44
Net Weight (kgs)	4.5
Net Weight (including accessories) (kgs)	7.5
ENVIRONMENT	
Operating Humidity	0-95 % RH @ -5°C- 45°C (non-condensing)

* Product specifications are subject to change without further notice