

## ADVICE GAMING UPS

- Display real-time Gaming PC performance data via USB port
- AVR for voltage stabilization
- **Spike protection- 645 Joules**
- **Pure sine wave**
- Diverse LED colors for selection
- Docking LCD design
- User-replaceable battery design
- Built-in USB communication port and RJ-45 surge protection
- Provides battery backup and surge protected outputs
- Optional Coax Surge Protection for TV antenna/network
- **3 years warranty for electronics, 2 years for battery**



### Specifications

Model	G-WAR1000-2	G-WAR1500-2
CAPACITY	1000 VA / 600 W	1500 VA / 900 W
INPUT		
Voltage	220/230/240 VAC	
Voltage Range	170~280VAC	
OUTPUT		
Voltage	220/230/240 VAC	
AC Voltage Regulation (Batt. Mode)	±10%	
Frequency Range (Batt. Mode)	50/60 Hz ±1 Hz	
Transfer Time	6ms typical, 10ms max	
Waveform (Batt. Mode)	Pure Sine Wave	
BATTERY		
Battery Type & Number	12 V/9 Ah x 1	12 V/9 Ah x 2
Typical Recharge Time	6~8 hours recover to 90% capacity	
INDICATORS		
LCD Display	Input/output voltage, input/output frequency, load in VA/Watts, battery capacity, estimated remaining runtime, site wiring fault indications.	
USB CHARGER		
USB Charger Ports	Type C X1 + Type A X1	
Output Voltage	5.2V±5%	
Load Current	3A(MAX)	
PHYSICAL		
Dimension, D X W X H (mm)	308 x 99 x 280	430 x 99 x 280mm
Net Weight (kgs)	9.2	13.8
ENVIRONMENT		
Humidity	0-90 % RH @ 0- 40°C (non-condensing)	
Noise Level	Less than 40dB	Less than 45 dB
MANAGEMENT		
USB Port	Supports Windows® 2000/2003/XP/Vista/2008/7, Linux, Unix, and MAC	
Compliance & Standards	CE , EN 62040-1:2008/A1:2013, IEC 62040-1:2008/A1:2013	

\* Product specifications are subject to change without further notice