

Partner Pro Series – Interactive UPS

Features:

- 1U high
- Including shutdown software for win
- The Led for batt mode, uses as emergency light.
- 1 AC output socket to protect accessories
- Microprocessor control
- No load self-shutdown at back-up mode (optional)
- Auto test function and diagnostics
- Low battery indicator
- DC Start available
- Short circuit protection
- SNMP Application (optional)
- On-line voltage regulation
- Line-interactive technology
- Full time surge suppression and noise filtering
- High efficiency in back up mode
- Smart charger for quick charging
- Detailed display on computer screen
- RS-232 communication port.
- Automatic frequency detection
- Protection on modem line or communication line



Specifications

19" Rack Mount Model		PRP1050RM
OUTPUT	VA rating	1000VA
	Wattage	600W
	Voltage	230VAC \pm 3% Regulation (inverter mode), 230VAC \pm 10% Regulation (mains mode)
	Wave form	Modified sine wave
INPUT	Voltage	230 vac \pm 25%
	Frequency	60Hz \pm 10%
TRANSFER TIME		2 ms typ
BATTERY	DC voltage	18V / 7Ah
	Type	Sealed lead acid
	Recharge time	3 to 5 hours
EFFICIENCY		95%
INDICATOR		On line- Green LED, On battery- Orange LED, Battery fail- Red LED
AUDIBLE ALARM		Battery in use, battery low, overload
TEST		Automatic testing by pressing power on, manual testing by Short press on power button
PROTECTION		Over current, short circuit, surge
SPIKE PROTECTION		Clamping voltage: 750V/50A, up to 320 jouels/2ms
CONNECTIONS	Input	IEC320 male
	Output	IEC320 female + Israeli receptacle
	Computer Interface	RS232
	10 base – T	Network, modem, surge protection port (RJ-45)
DIMEENSION (wxhxd) mm	19" RACK MOUNT MODEL	483X44X362 (1U)
NET WEIGHT (Kgs)	19" RACK MOUNT MODEL	10.5
ENVIRONMENT	Operating Temperature	0-45°C
	Humidity	0-95% non-condensing
	Standarts	CE

* Product specifications are subject to change without further notice