

SNMP-TOP V / SNMP-MCY-EN

Features:

- Allows control and monitoring of multiple UPSs through RJ-45 ethernet port
- Built-in web server
- Real-time dynamic graphs of UPS data (voltage, frequency, load level, battery level)
- Warning notifications via audible alarm, broadcast, mobile messenger, e-mail and SNMP traps
- Historic data log stored in centralized PC database
- Simple firmware upgrade with one click
- Password security protection and remote access management
- Supports optional environmental monitoring detector for Temperature & humidity



Specification

Model	SNMP-TOP V / SNMP-MCY-EN
Protocol Support	TCP/IP, UDP,SNTP, HTTP, DHCP, SNMP v1/2/3,SMTP
UPS Slot Type	Golden Finger
Network Support	RJ45 10/100BaseT
Supported MIB	RFC1213, RFC1628, Voltronic MIB
Supported Software	ViewPower Pro and SolarPower Pro
Supported OS	Windows family, Liunx and MAC
Supported Extension Devices	Optional environmental monitoring detector
Power Consumption	3 watt (max.)
Operating Temperature	0 ~ 55°C
Operating Humidity	0 ~ 95%
Dimension, D X W X H (mm)	80 x 26 x 52
Net Weight	0.11 kgs

* Product specifications are subject to change without further notice