



## Slab Extractor PZ

For extracting single slabs, it has a robust construction so that the blades can be hammered into the joints.

- With Locking Device. The operator does not need to continually squeeze the PZ-handles together!
- Adjustable without tools.
- Complete with easily exchangeable high-quality-special double spring-steel blades.
- Galvanised finish.

PZ

Type	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
PZ	6 (13)	200 – 610 (7.87 – 24.02)	70 (154)	53200006

### Spare Parts:

Type	Description	Dead Weight kg (lbs)	Order-Number
Spare blade short	(55 mm / 2.16 inch) per piece, loose	0.04 (0.088)	41800001
Spare blade short	(55 mm / 2.16 inch) 2 pieces in blister pack	0.08 (0.18)	41800242
Spare blade long	(65 mm / 2.55 inch) per piece, loose	0.04 (0.088)	41800003
Spare blade long	(65 mm / 2.55 inch) 2 pieces in blister pack	0.09 (0.20)	41800243



## SAFEFLEX SF

The innovative clamping fixture for cutting stone safely.

The risk of cuts can be reduced considerably with the SAFEFLEX SF. It can secure building materials such as cobblestones and natural flagstones quickly and safely. This makes cutting with the angle grinder easier, safer and more precise.

To secure the building material, the user pushes on the top clamping element with one foot. When the user takes their foot off the non-slip tread, springs push the clamping elements apart again and the building material can be removed.

- Elevation of the material being cut, so cutting wheel does not go into the ground.
- Non-slip mat to prevent stones from sliding sideways.
- Fast and simple adjustment of stone thickness in using 2 lateral locking bars.
- Individually adjustable height of the SAFEFLEX with 4 screws that can be turned in on the bottom.
- Suitable for right and left-handed use.
- Fast fixation without additional tools.
- Saves material since smaller "offcuts" can be safely secured, even with a small supporting surface.
- Easy to transport since the SAFEFLEX is much smaller than a wet cutting bench for example.
- Durable surface protection by galvanizing.

SF



Type	Dead Weight kg (lbs)	Height Adjustable Range mm (in)	Clamping Range mm (in)	Order-Number
SF	7.46 (16)	10 (0.39)	30 – 160 (1.18 – 6.30)	51210001