



AW-60

Aluminium Angle AW

For precise alignment of interlocking paving stones.

Operating angles: 45° and 90°.

Foldable.

Type	Dimensions L x W mm (in)	Dead Weight kg (lbs)	Order-Number
AW-60	600 x 800 (23.62 x 31.49)	0.72 (1.59)	51800052
AW-120	1,200 x 1,200 (47.24 x 47.24)	1.7 (3.75)	51800085



FMK

FLEXMARKER-KIT FMK

The FLEXMARKER-KIT FMK is a complete system to shape and mark tailor-made curves. Creating dynamically shaped paths without visual interruptions.

Work mode 1: For paths and bed edges, the so called one-liner, are laid in dry concrete. For that purpose the FLEXMARKER-KIT FMK can be fixed at the pins with the clamps. It doesn't only show the curve, it also shows the vertical profile.

Work mode 2: The interconnecting fiberglass rods can be securely fixed on the existing pavement with the fixing claws. The curve can be marked by spray paint or chalk (e.g. PAVERMARKER PM of Probst). Weighted by paving stones, the claws are immovably fixed.

- Harmonious curves can be prepared quickly and with enormous time savings.
- Smallest bending radius 15 cm (6 inch).

Scope of delivery:

FMK: Set consisting of 10 fiberglass rods, 5 fixing claws and 10 clamps.



FMK

Type	Dead Weight kg (lbs)	Order-Number
FMK	3.1 (6.83)	51800074