

COMPACTCUT 202 E

LISSMAC

CONSTRUCTION TECHNOLOGY

ROBUST, HIGH-PERFORMANCE ELECTRIC FLOOR SAW –
IDEAL FOR CUTTING WORK INSIDE BUILDINGS

- Floor saw in robust and compact construction
- The smooth raising and lowering of the saw blade with a closed threaded spindle prevents damaging of the saw blade
- Adjustable cutting depth indicator for all saw blade diameters
- A large water tank reduces work interruptions
- The water cooling system provides an optimum saw blade cooling, this guarantees a longer saw blade life
- Blade guard easily foldable
- Simple service operations - good access to engine and cutting shaft
- With a parking brake
- Height adjustable handles for ergonomic operation
- Connection for external water supply with separately adjustable water tap
- The anti-vibration handle reduces vibrations to the operator, improving working conditions.



TECHNICAL DATA	COMPACTCUT 202 E
cutting depth max.	200 mm
cutting depth setting	stepless threaded spindle with depth gauge
saw blade Ø max.	500 mm
saw blade holder	25.4 mm
drive motor	electric
output power max.	5 kW
voltage	400V / 32 A
saw blade speed	2450 1/min.
dimensions (L/W/H)	1195/620/1010 mm
weight	115 kg



DIAMOND TOOLS RECOMMENDATION

Asphalt	ASW 11
Concrete	BSW 12

FLOOR SAWS	NR.
COMPACTCUT 202 E without diamond blade, incl. blade guard 500 mm	1094058
TOOLS	NR.
ASW 11 diamond blade Ø 450 mm / 25,4 mm for asphalt	1054980
ASW 11 diamond blade Ø 500 mm / 25,4 mm for asphalt	1054982
BSW 12 diamond blade Ø 450 mm / 25,4 mm for concrete	1070155