





TECHNICAL SPECS	
Voltage	460V
AMPS	29A
Power Output	20hp (15kW)
Phase	3-Phase
Weight	1185 lbs (538kg)
Cycles	60Hz
Head Speed	0 - 1033 rpm
Motor Speed	0 - 1765 rpm
Grinding Plate Speed	0 - 110 rpm
Grinding Width	32" (81cm)
Head Diameter	10.5" (27cm)
Water Tank	7 gal (27L)
Hose Size	3" (75mm)
Length	57" (145cm)
Width	33" (83cm)
Height	52" (132cm)

THE PREDATOR SERIES DELIVERS AGGRESSIVE GRINDING & PERFECT POLISHING IN ONE GREAT MACHINE

The secret of the Predator's success is the planetary motion, which eliminates the swirl marks left by conventional grinding methods. These grinders are manufactured with the highest standards in the industry, making them extremely reliable, productive, balanced and easy to use for any operator.

With the addition of the versatile weight package and the new drive system (NDX), the P32NDX is ready to handle the toughest grinding jobs and polish floors with ease.

FEATURES

- · 32" working width
- · 4-head planetary design
- · Variable speed
- · Forward & reverse setting
- · American made
- · Belt driven
- · High production rates
- · Swing weight & travel wheel available
- · Uses SlideMag quick-change diamond tooling
- · Fully compatible with the iShine Floor System
- · Simple adjustment to level to the floor surface
- · Dust-free when used with suitable dust extractor







P2400

P32N

P32NDX

