



Tray Ledge Replacement Instructions (#31, 32)




What's Included:

4 Tray Ledge Pieces,
Screws



Tools Needed: Phillips screwdriver, drill, utility knife, **OR** putty knife

1. Determine how your Tray Ledge was installed.
 - a. If your Tray Ledge is installed with screws, use a Phillips screwdriver or a drill, unscrew your damaged Tray Ledge and discard. (Figure 1)
 - b. If your Tray Ledge was installed behind the metal trim, use a utility knife to cut the tray rail from the trunk. (Figure 2)
 - c. If your Tray Ledge was installed with two-sided tape, you will use a putty knife to pull the broken ledge off of the trunk. You will see a small gap between the Tray Ledge and the trim. (Figure 3)
2. You will receive 4 pieces of replacement Tray Ledge. Assemble the replacement Tray Ledge by connecting the Ledge with the dowel into a Ledge without a dowel (Do this for both sets). (Figure 4) You should have two pieces, one for the front and one for the back of the trunk.
3. Remove the backing from the four pieces of tape on the back of the Tray Ledge. Hold the Tray Ledge with your fingertips positioned on the bottom of the Tray Ledge below the tape and your thumbs on the front edge of the Tray Ledge. (Figure 5)
4. Center the Tray Ledge on the back wall of the trunk two inches from the trim at a 90° angle. Drag the Tray Ledge up until it contacts the metal trim. Verify it is still roughly centered. Gently tip the Tray Ledge down so it's in the fixed position. Apply pressure along the back of the Tray Ledge to adhere the Tray Ledge tape to the back of the trunk. Repeat for the front Tray Ledge. You can use the included screws to reinforce the Tray Ledge.



Call Everything Summer Camp at 1-800-535-2057 if you have any questions.