

Ludlum

Ludlum 192 Micro Rad Meter

Pine Item # 54483

DESCRIPTION:

The Ludlum 192 Micro R Meter is a low level (Micro R) gamma meter. It features 4 ranges, auto adjust alarm settings and 2' x 1' sodium iodide (nal) T1 scintillator.

The 192 Micro R Meter's sensitivity typically is 700 cpm/microR/hr (Cs-137 gamma).

This unit is micro-processor based and has total counting range from 0-5,000 μ R/hr.

FEATURES:

- Reset: Push-button to zero meter and also re-accumulate background data and recalculate the alarm deviation.
- Response: Toggle switch fro FAT (4 seconds) or SLOW (22 seconds) from 10% to 90% of final reading.



Contact a Pine branch near you to request a quote or place an order

VISIT OUR U.S. AND CANADA WEBSITES TO FIND A BRANCH NEAR YOU

United States

www.pine-environmental.com

Canada

www.pine-environmental.ca

Product Specifications

Audio	Built in unimorph speaker with ON/OFF switch (greater than 60 dB at 2 feet)
Temperature Range	-4°F (-20° C) to 122°F (65°C)
Power	2 each "D" cell batteries (housed in sealed compartment that is externally accessible)
Meter	2.5" (6.4cm) arc 1 mA analog type
Battery Life	Typically 600 hours with alkaline batteries. Battery condition 600 hours with both alka
Dimension	US: 7.8 H x 3.5" W x 8.5" L" Metric: 19.8 cm H x 8.9cm x 21.6 cm L
Weight	US: 4.5 lbs Metric: 2.1 kg




Video:
<https://youtu.be/cm1YiISq-I3s>



Local Delivery Pick-up



In-Stock Equipment



Repair & Calibration



Rental Protection Plan