

Magnetic Crawlers - Visual Inspection Remote Visual Inspection (RVI)







Eddyfi

Inuktun VT100 MKII Crawler System

Pine Item #55906

DESCRIPTION:

Inuktun's Versatrax 100[™] Mark II is a miniature pipe inspection system with a variety of configurations that can tackle almost any confined space inspection application. Offering full modularity, the Mark II can be arranged either inline for small diameters, in parallel configuration for larger pipes and ductwork, or with a magnetic attachment for vertical and inverted travel on ferrous surfaces.

With this latest design, you can connect a camera directly to the tether cable, so it also works as a standalone inspection camera too. And it is truly portable; the entire system can be packaged in hard shell industrial carry cases making it easy to transport and quick to set up in almost any environment.

FEATURES:

- Depth Rating: 60m / 200ft
- Maximum Tether Length: 300m / 1000ft
- Maximum Speed: 9m / 30ft per minute
- Vehicle Payload: up to 4.5kg / 10lb
- Front Facing Camera: Spectrum 45
- Operating Temperature: 0°-40° C / 32°-122° F

APPLICATIONS:

- Municipal (Sewer/Water)
- Nuclear
- Oil & Gas (Onshore/Offshore)
- Petrochemical
- Tank Inspection (Internal/External)
- Subsea/Ship Hull Inspection
- Well/Caisson Inspection (Drop Camera Operation)

Contact a Pine branch near you to request a quote or place an order

VISIT OUR U.S. AND CANADA WEBSITES TO FIND A BRANCH NEAR YOU

United States www.pine-environmental.com Canada www.pine-environmental.ca

Product Specifications

Depth Rating	60m / 200ft
Maximum Tether Length	300m / 1000ft
Maximum Speed	9m / 30ft per minute
Vehicle Payload	up to 4.5kg / 10lb
Front Facing Camera	Spectrum 45
Operating Temperature	0°-40° C / 32°-122° F
Standard Components	2 x 4000 series Microtracs 1 x Spectrum 45 camera auxiliary LED lights (parallel vehicle) inline and / or parallel chassis and wiring harness 100m / 330ft tether ICON Pro with InPRO editing software control system and interface box.
Dimensions	US: 33x4x4in (inline) 13x7x6in (parallel) Metric: 848x100x100mm (inline) 331x170x150mm (parallel)
Weight	US: 15 lb Metric: 6.8 kg







Repair & Calibration



Local Delivery Pick-up

In-Stock Equipment

Rental Protection Plan

www.pine-environmental.com