



Project	
Notes	
Type	Date
Cat. No.	

**DOW™ Series**

**Decorative Outdoor Pocket Lantern**



**DOW Series**

9W, 800 Lumens  
11W, 1100 Lumens

Rated Life 60,000 hours  
Limited Warranty 3 years  
Efficacy Up to 100 LPW

**Quick Ship**

Made To Order Only

**DESCRIPTION**

The DOW LED wall light combines high-performance LEDs, a weather resistant aluminum housing along with a frosted glass diffuser for uniform illumination. Ideal use for security and general lighting. Provides lighting in residential, commercial, and hospitality applications.

**Specification Features**



**Construction**

Rugged die cast aluminum housing withstands outdoor environments. Outer surface treated with durable power coating to provide resistance to corrosion, rust, weathering, and or degradation. Performance engineered internal heat dissipation fins provide superior thermal management for LED life and reliability.

**Qualifications**

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. ENERGY STAR® certified product (for 3000K and 4000K only). Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications.

**Electrical**

120V Driver operates at 60Hz.

**Installation**

Designed for mounting on 4" electrical J-Box.

**Warranty**

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

**Ordering Information**

Example:DOW-9-120-850

DOW	11	120	8	50	BL	P
<b>Series</b> DOW Decorative Outdoor Pocket Lantern	<b>Rated Wattage</b> 9-9W, 800 Lumens <sup>1</sup> 11-11W, 1100 Lumens <sup>1</sup>	<b>Driver Type</b> 120- 120V <sup>1</sup>	<b>CRI</b> 8 80+ CRI	<b>Color Temperature</b> 30 3000 K <sup>1</sup> 50 5000 K <sup>1</sup>	<b>Driver Finish</b> BL- Black <sup>1</sup>	<b>Options</b> P- Photocell <sup>1</sup>

Specifications and Dimensions subject to change without notice.

## Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	> 100 LPW (typ.)
CRI	80+, R9 > 0
Available CCT <sup>1</sup>	3000K, 5000K
Color Consistency <sup>2</sup>	5-step MacAdam Ellipse
Rated Life	60,000 hours
L70 <sup>3</sup>	> 72,000 hours or > 45,000
Power Factor	>0.99
THD	< 20%
Dimming	N/A
Operating Temp.	-18°C to 40°C

## Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Acrylic		DOW-9-120-850	9W	800	88.8
		DOW-11-120-850	11W	1,100	100

### NOTES:


- <sup>1</sup> Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- <sup>2</sup> Energy star listed
- <sup>3</sup> Quick ship: 3000K,5000K. Other CCTs may require a lead time or be special order
- <sup>4</sup> Typical color consistency. May vary or be changed.
- <sup>5</sup> L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information
- <sup>6</sup> Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications and Dimensions subject to change without notice.



## Product Dimensions

DOP



**GlobaLux**  
LIGHTING

© 2019 GlobaLux Lighting, LLC. All rights reserved. For informational purposes only. Reproduction in whole or part is prohibited without prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequences of its use. GlobaLux Lighting reserves the rights make changes in specification at any time without notice.

**GlobaLux Lighting LLC**  
www.globaluxlighting.com  
2037 S. Vineyard Ave  
Ontario, CA 91761  
Ph: 909-591-7506