



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE

### LED 2 Ringed Ceiling Fixture

The 2 Ringed Ceiling Fixture is a ceiling or wall mount that can be used in a broad range of residential and commercial applications. This series provides customers with a high quality luminaire utilizing the latest LED, solid-state lighting and electronic driver technology for optimal performance and maximized energy efficiency. With a traditional opal white lens, the DCR series produces even, uniform light distribution and an ideal choice for offices, corridors, stairways, bedroom, closet, and foyer applications where customers are replacing incandescent, circling or compact fluorescent lamps.

### Features

High transmission white acrylic lens with excellent distribution and uniformity. Full distribution LED luminaire with 10-100% triac dimming, compatible with most triac dimming switches. 120V AC with Driver on Board Technology designed for a 50,000-hour life. Highly efficient diodes produce little heat. Designed to cast light downwards in an environmentally friendly manner.

### Construction

Contemporary slayed fixture. Twin steel rings surround a milk white acrylic diffuse provides widespread and even illumination.

### Electrical

Equipped standard with 120V 10 -100% triac dimming driver, operating at 60Hz.

### Certification

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. Dedicated 120V Models are FCC Title 24 CFR, Part 15, Class B for residential and commercial applications. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications. California Title 24 compliant, JA8 compliant, CEC listed.

### Warranty

5-year limited warranty. See complete warranty for terms and conditions (labor not included.)

### Ordering Information

Model Number	Voltage	Wattage	CRI	Lumens	CCT	Dimmable	Size
I2RC-1212-120D-930NS	120V	12W	90	956	3000	Triac 10-100%	12"
I2RC-1417-120D-930NS	120V	17W	90	1700	3000	Triac 10-100%	14"

