



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE

LED Flood Light

The LED Flood Light utilizes precision optics to beautifully illuminate a range of applications while its ultra slim form factor blends seamlessly with the environment. The flood reflector systems and SMD technology produce excellent uniformity and exceptional photometric performance. Offering style in a simple way, this fixture is ideal for extra home security and peace of mind.

Features

Constructed of durable low profile aluminum alloy housing that withstands outdoor environments. Patented Ultra Slim, Elegant, and Distinctive Form Factor. High performance, long lasting SMD LEDs with high lumen output, provides 50,000 hour average life making the fixtures virtually maintenance free. Instant start that is flicker free. An IP rating of IP65. Resistance to wet locations makes it recommended for outdoor use.

Construction

Two tool-free adjustable heads allow for easy aiming up/down or side to side. Rugged cast aluminum, corrosion-resistant housing in bronze or white. Clear acrylic lenses are fully gasketed to keep out moisture, dirt, and bugs.

Electrical

Equipped standard with 120V fixed output driver, operates at 60Hz.

Certification

All luminaires are built to UL 1598 and 2108 standards and bear appropriate ETL labels. Wet location labeling is standard.

Warranty

5-year limited warranty. See complete warranty for terms and conditions (labor not included.)

Ordering Information

Model Number	Voltage	Wattage	CRI	Lumens	CCT	Dimmable	Size
IFL-20-MV-840	120V-277V	20W	80	2000	5000	-	One Size
IFL-50-MV-850	120V-277V	50W	80	5500	5000	-	One Size

