



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE

LED Premium Wrap

This wraparound fixture is a cost effective and energy-saving replacement for less efficient fluorescent wrap-around fixtures. The wrap fixture features a full length U-wrap frosted Acrylic lens and a one-piece fabricated steel body. These LED wrap around fixtures are ideal for lighting in parking garages, stairwells, and/or to help you meet applicable building and safety codes in residential multi-family buildings, workshops, utility rooms, corridors, and other commercial applications.

Features

Steel construction with thermal/lumen balanced light engines. Has back and end knockouts which allow it to be ceiling or wall mounted. Low power consumption with 4000 kelvin color temperature being the standard. Optional On/off or bi level motion sensor, high voltage transformers, emergency battery backups, cords, and whips. For covered use only – damp rated.

Construction

Rugged construction, solid die formed, cold-rolled steel housing. All surfaces powder coated after fabrication. Frosted Acrylic diffusers provides even consistent light while reducing glare. Lens design and materials provide uniform appearance without pixilation.

Electrical

Equipped standard with a 0-10V continuous driver that works with any standard 0-10V control/dimmer. Long-life LED's 60,000 hours at L80 with projected life over 100,000 hours for reduced life cycle maintenance costs.

Certification

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. Design Lights Consortium (DLC) qualified product. Not all models of this product may be DLC qualified. Please check the DLC product list at www.designlights.org/QPL.

Warranty

5-year limited warranty. See complete warranty for terms and conditions (labor not included.)

Ordering Information

Model Number	Voltage	Wattage	CRI	Lumens	CCT	Dimmable	Size
IPW-4840-MVD-840	120V-277V	52W	80	4000	4000	0-10V	48"

