

LOCATION	DATE
PREPARED	QUANTITY
COMMENTS	
	FIXTURE TYPE

LED Ringed Light Vanity

The IRWS series features two weeks of twin steel rings surrounded a frosted glass diffuser designed to eliminate glare and optimize lumen output. Clean lines are up front and center for these modern LED sconces. Energy efficient LED source offers 3000K color temperature and 90+CRI output.

Features

High-transmission frosted glass lens with excellent distribution and uniformity. A direct replacement for fluorescent. Clean lines are central to design. Full distribution LED luminaire. Suitable for damp locations.

Construction

Contemporary styled fixture. Twin steel rings surround a frosted glass diffuser designed to eliminate glare and optimize lumen output.

Electrical

Equipped standard with a 120-277V driver. Average hour life of 50,000 hours.


Certification

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. Dedicated 120V models are FCC title 47 CFR, Part 15, Class B for residential and commercial applications. California title 24 compliant, JA8 compliant, CEC listed.

Warranty

5-year limited warranty. See complete warranty for terms and conditions (labor not included.)









Ordering Information

Model Number	Voltage	Wattage	CRI	Lumens	CCT	Dimmable	Size
IRWS-129-MV-930	120V	9W	90	515	3000	-	12"