



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE

**LED Shoebox area (Parking Lot)**

Our Shoebox Parking lot light is an energy efficient LED area light. Intended to replace a 250W or 400W metal handle area light. Re-lamping once every 12- 15 years. Instead of every 6 months makes this an attractive fixture for new construction and retrofit lighting upgrades. Perfect for hard to service locations. Rugged die cast design ensures LED's operate at optimum temperature for long life. Sealed to the environment for long reliable service life.

**Features**

Sturdy weather-resistant bronze aluminum housing with Silicone casketing providing protection against moisture. Adjustable dusk-to-dawn photocell automatically turns light on at dusk and off at dawn for convenience and energy savings. The photocell can be disabled with one turn on its cover. Optional On/Off or bi-level motion sensor, high voltage transformers, emergency battery backups, cords and whips.

**Construction**

Rugged die cast aluminum housing withstands outdoor environments. Outer surface treated with durable powder coating to provide resistant to corrosion, rust, weathering, and or degradation. Performance engineer internal heat dissipation fins provide superior thermal management for lens life and reliability.

**Electrical**

Equipped standard with fixed output driver. Long life LED's 60,000 hours at L80 with projected life over 100,000 hours for reduced life cycle maintenance costs.

**Certification**

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. Design lights Consortium (DLC) qualified product. Not all models of this product may be DLC qualified. Please check the DLC product list at [www.designlights.org/qpl](http://www.designlights.org/qpl).

**Warranty**

5-year limited warranty. See complete warranty for terms and conditions (labor not included.)

**Ordering Information**

Model Number	Voltage	Wattage	CRI	Lumens	CCT	Dimmable	Size
ISB-100-MV-850-SF/SPM	120V-277V	100W	80	16,608	5000	-	One Size
ISB-150-MV-850-SF/SPM	120V-277V	150W	80	24,913	5000	-	One Size
ISB-200-MV-850-SF/SPM	120V-277V	200W	80	33,217	5000	-	One Size

