



LED Square Canopy

The LSC family of LED canopy fixtures combine high-performance LEDs, highly-engineered optics to traditional designs to bring you the most advanced line of canopy fixtures on the market. The long LED life coupled with exceptional color rendering make this fixture attractive for new or retrofit projects. Multiple lumen packages mean there is an LSC that is just right for your lighting needs.

Features

A sturdy, weather resistant aluminum housing makes the canopy ideal for outdoor use. Easy to replace HID Canopy Light. Direct replacement of fluorescent long-life, 60,000 hour LEDs at L80 reduce lift cycle maintenance costs. Adjustable dusk-to-dawn photocell automatically turns light on at dusk and off at dawn for convenience and energy savings. The photocell can be disabled with one turn on its cover. Optional On/Off or bi-level motion sensor, high voltage transformers, emergency battery backups, cords, and whips.

Construction

Rugged die cast aluminum housing withstands outdoor environments. Outer surface treated with durable powder coating to provide resistant to corrosion, rust, weathering, and or degradation. Performance engineer internal heat dissipation fins provide superior thermal management for lens life and reliability.

Electrical

Can be equipped standard with 0-10V continuous dimming driver that works with any standard 0-10V control/dimmer. Long life LED's 60,000 hours at L80 with projected life over 100,000 hours for reduced life cycle maintenance costs.

Certification

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. Design lights Consortium (DLC) qualified product. Not all models of this product may be DLC qualified. Please check the DLC product list at www.designlights.org/qpl.

Warranty

5-year limited warranty. See complete warranty for terms and conditions (labor not included.)

Ordering Information

Model Number	Voltage	Wattage	CRI	Lumens	CCT	Dimmable	Size
ISC-40-MV-850	120V-277V	40W	80	5,480	5000	-	12 X 12
ISC-70-MVD-850	120V-277V	70W	80	11,072	5000	0-10V	12 X 12

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE

