



LED Undercabinet Fixture

IUC LED's are a fast and easy solution for lighting in commercial, retail, hospitality, and residential applications, Ideal for use under and over cabinets, display cases, task lighting, office lighting, coves, and utility/work areas. Standard knockouts are located on top, back, or ends for direct connection. Sections can operate independently or be linked to one another and are dimmable.

Features

Made with a high-transmission (white) acrylic lens with excellent distribution and uniformity. Four finishes are available (white, black, nickel, and oil-rubbed bronze.) Hard-wire connections keep a low profile at 120V. A hinged wire-way cover with optional rocker switch. Can switch between 3000 or 4000 kelvin color temperature.

Construction

Low profile steel housing available in white, nickel, satin, or oil rubbed bronze finishes. Designed to prevent "hot spots" on counter tops. Lens design and materials provide uniform appearance without pixilation.

Electrical

Equipped standard with f120V 15-100% triac dimming driver operating at 60Hz.

Certification

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. Dedicated 120V models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications. California Title 24 compliant, JA8 compliant, CEC listed.

Warranty

5-year limited warranty. See complete warranty for terms and exclusions (labor not included.)

Ordering Information

Model Number	Voltage	Wattage	CRI	Lumens	CCT	Dimmable	Size
IUC-95-120D-930/40WH	120V	5W	90	373	3000/4000	Triac 15-100%	9"
IUC-125-120D-930/40WH	120V	5W	90	373	3000/4000	Triac 15-100%	12"
IUC-189-120D-930/40WH	120V	9W	90	678	3000/4000	Triac 15-100%	18"
IUC-219-120D-930/40WH	120V	9W	90	678	3000/4000	Triac 15-100%	21"
IUC-249-120D-930/40WH	120V	9W	90	678	3000/4000	Triac 15-100%	24"
IUC-3314-120D-930/40WH	120V	14W	90	1051	3000/4000	Triac 15-100%	33"
IUC4218-120D-930/40WH	120V	18W	90	1245	3000/4000	Triac 15-100%	42"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE

