



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE

LED Wall Pack

The most advanced line of wall packs on the market. Designed and engineered as maintenance free, energy efficient alternatives to traditional fluorescent, high-pressure sodium and HID light sources. Multiple lumen packages mean there is a wall pack that is just right for your lighting needs.

Features

Sturdy, weather resistant aluminum housing. Silicone gasket provides protection against moisture. Direct replacement of fluorescent long-life, 60,000 hour LEDs at L80 reduce lift cycle maintenance costs. Adjustable dusk-to-dawn photocell automatically turns light on at dusk and off at dawn for convenience and energy savings. Clear prismatic borosilicate lens is thermal/shock resistant. Optional On/Off or bi-level motion sensor, high voltage transformers, emergency battery backups, cords, and whips.



Construction

Rugged die cast aluminum housing withstands outdoor environments. Outer surface treated with durable power coating to provide resistant to corrosion, rust, weathering, and or degradation. Performance engineer internal heat dissipation fins provide superior thermal management for lens life and reliability.

Electrical

Equipped standard with fixed output driver. Long life LED's 60,000 hours at L80 with projected life over 100,000 hours for reduced life cycle maintenance costs.

Certification

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. Design lights Consortium (DLC) qualified product. Not all models of this product may be DLC qualified. Please check the DLC product list at www.designlights.org/qpl.

Warranty

5-year limited warranty. See complete warranty for terms and conditions (labor not included.)

Ordering Information

Model Number	Voltage	Wattage	CRI	Lumens	CCT	Dimmable	Size
IWP-50-MV-850	120V-277V	50W	80	7,200	5000	-	One Size
IWP-80-MV-850	120V-277V	80W	80	9,600	5000	-	One Size
IWP-100-MV-850	120V-277V	100W	80	12,000	5000	-	One Size

