

ETC-1808-s Description & Specifications



Features

- 18 AWG 8 Conductor Stranded Shielded
- 500ft pull boxes
- White Jacket
- Cost Effective


Description

This 18-gauge stranded shielded cable is perfect for refrigeration and HVAC EMS sensor installations and other low voltage electrical applications. Use ETC's EMS sensor cable to connect temperature and humidity sensors, door sensors, pressure transducers and refrigerant leak detectors to Emerson, Danfoss, Micro-Thermo systems and other EMS systems.

ETC-1808-s Specifications

-	-	
Conductor	AWG	18AWG
	QUANTITY	8 Conductor
	MATERIAL	CCAG
	CONSTRUCTION	Stranded
	CONDSIZE	7/0.40±0.008mm
Insulation	AVG.	0.20mm
	MATERIAL	HDPE
	COLOR	Red, Black, Green,
		Yellow, Blue, White,
		Orange, Brown
	ID	1.6 ± 0.05 mm
Drain	OD	7/0.40±0.008mm
	MATERIAL	CCAG
AL-Foil	SIZE	20x0.035mm
Jacket	MATERIAL	PVC
	AVG.	0.45mm
	COLOR	White
	OD	5.8 ± 0.2 mm
Cable Marking	XXXXFT 18AWG/8C STRANDED SHIELDED CL2(ETL VERIFIED) RoHS ISO9001	

Cross Section:



Revision 2022-11-02