





	Double temperature island Cabinet(with door)			Double temperature island Cabinet(without door)		
						
Model	HIT-7	HIT-8	HIT-3	HIT-10	HIT-11	HIT-12
Product identification						
Product description	Double temperature island Cabinet					
Cooling system (Static / No Frost)	VENTILATDE	VENTILATDE	VENTILATDE	VENTILATDE	VENTILATDE	VENTILATDE
Refrigeration type	F	F	F	F	F	F
Climate class (3= 25°C, 60%RH)	3	3	3	3	3	3
Temperature range	L1/M1	L1/M1	L1/M1	L1/M1	L1/M1	L1/M1
Key features						
Total net capacity(L)	215	290	370	215	290	370
Display Area(M2)	1.81	2.36	2.91	1.81	2.36	2.91
Defrosting (Manual-Automatic)	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Kind of coolant(R134a/R404a/R600a)	R290	R290	R290	R290	R290	R290
Foaming components	C-P	C-P	C-P	C-P	C-P	C-P
Technical data						
Voltage / frequency/Phase	115-230v/50-60hz/1ph	115-230v/50-60hz/1ph	115-230v/50-60hz/1ph	115-230v/50-60hz/1ph	115-230v/50-60hz/1ph	115-230v/50-60hz/1ph
Input power(W)	900	1200	1500	900	1200	1500
Compressor power(W)	640	850	1070	640	850	1070
Frost power(W)	1500	2100	2400	1500	2100	2400
Safety class	I	I	I	I	I	I
Thickness of cabinet walls (mm)	56-95	56-95	56-95	56-95	56-95	56-95
Operating current(A)	6	8	10	6	8	10
Defrost	Automatic(hot gas)	Automatic(hot gas)	Automatic(hot gas)	Automatic(hot gas)	Automatic(hot gas)	Automatic(hot gas)
Defrost per day NO	3	3	3	3	3	3
Max deforst length minutes	20(freezer)/25(chiller)	20(freezer)/25(chiller)	20(freezer)/25(chiller)	20(freezer)/25(chiller)	20(freezer)/25(chiller)	20(freezer)/25(chiller)
Equipment & accessories						
Inside walls	Prepainted aluminum	Prepainted aluminum	Prepainted aluminum	Prepainted aluminum	Prepainted aluminum	Prepainted aluminum
Type of door	sliding door	sliding door	sliding door	without	without	without
Number of glass door	3	4	5	without	without	without
Compressor	Embraco*2	Embraco*2	Embraco*2	Embraco*2	Embraco*2	Embraco*2
Evaporator	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin
Evaporator fan	Sanju	Sanju	Sanju	Sanju	Sanju	Sanju
Condensor	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin
Condensor fan	Yongrong	Yongrong	Yongrong	Yongrong	Yongrong	Yongrong
Heater in door frame for anti-icing	Without	Without	Without	Without	Without	Without
Lock	Without	Without	Without	Without	Without	Without
Baskets Divider for super market	Without	Without	Without	Without	Without	Without
Defrost drain	High-pressure tube+heater	High-pressure tube+heater	High-pressure tube+heater	High-pressure tube+heater	High-pressure tube+heater	High-pressure tube+heater
Interior light	Option	Option	Option	Option	Option	Option
Price tag	NO	NO	NO	NO	NO	NO
thermostat	Hongke	Hongke	Hongke	Hongke	Hongke	Hongke
Type of Throttle	Capillary Tube	Capillary Tube	Capillary Tube	Capillary Tube	Capillary Tube	Capillary Tube
Plug (G/JK/IT/CH/EU)	On your optional	On your optional	On your optional	On your optional	On your optional	On your optional
Adjustable feet	YES	YES	YES	YES	YES	YES
Product net dimensions						
Inside dimension (W / D/ H)(mm)	1390*760*360	1890*760*360	2390*760*360	1390*760*360	1890*760*360	2390*760*360
Unit dimensions (W / D/ H)(mm)	1500*951*895	2000*951*895	2500*951*895	1500*951*895	2000*951*895	2500*951*895
Packing dimensions & loadability						
Packing	Wood base + wood frame	Wood base + wood frame	Wood base + wood frame	Wood base + wood frame	Wood base + wood frame	Wood base + wood frame
Packing dimensions (W / D/ H)(mm)(wood frame)	1620*1080*1130	1620*1080*1130	1620*1080*1130	1620*1080*1130	1620*1080*1130	1620*1080*1130
Packing	Plywood base+all plywood	Plywood base+all plywood	Plywood base+all plywood	Plywood base+all plywood	Plywood base+all plywood	Plywood base+all plywood
Packing dimensions (W / D/ H)(mm)(all plywood)	1580*1030*1130	2080*1030*1130	2580*1030*1130	1580*1030*1130	2080*1030*1130	2580*1030*1130