

										
model		HIT-13	HIT-14	HIT-15	HIT-16	HIT-17	HIT-18	HIT-19	HIT-20	
2.	Product identification									
	Cooling system (Static / Ventilated)	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	
	Climate class (3= + 25°C, 60%RH)	3	3	3	3	3	3	3	3	
3.	Key features									
	Effective Volume	(ft3)	13.6	18	20.8	32.7	12	15	18	28
	Effective Volume	(L)	385	512	590	925	336	448	516	810
	Display Area	(ft2)	21.3	25.4	28.2	32	21.3	25.4	28.2	32
	Display Area	(m²)	1.98	2.36	2.62	2.98	1.98	2.36	2.62	2.98
	Defrosting (Manual-Automatic)		Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
	Kind of coolant (R134a/R404a/R600a)		R290	R290	R290	R290	R290	R290	R290	R290
	Foaming components		C-P	C-P	C-P	C-P	C-P	C-P	C-P	C-P
	Max noise level		Max:70	Max:70	Max:70	Max:70	Max:70	Max:70	Max:70	Max:70
	Technical data									
4.	Voltage / frequency	V/Hz	110V/60HZ	110V/60HZ	110V/60HZ	220V/60HZ	110V/60HZ	110V/60HZ	110V/60HZ	220V/60HZ
	Temperature range	From-to, n°F	M2(30.2-44.6)	M2(30.2-44.6)	M2(30.2-44.6)	M2(30.2-44.6)	M2(30.2-44.6)	M2(30.2-44.6)	M2(30.2-44.6)	M2(30.2-44.6)
	Temperature range	From-to, n°C	M2(-1-7)	M2(-1-7)	M2(-1-7)	M2(-1-7)	M2(-1-7)	M2(-1-7)	M2(-1-7)	M2(-1-7)
	Safety Class		I	I	I	I	I	I	I	I
	current	A	15	28	30	18	15	28	30	18
	Interior input power	W	1450	2750	2900	3500	1450	2750	2900	3500
	Power consumption	KW*24H	26	38	48.5	56	26	38	48.5	56
	Aesthetics									
	Top cover Light box		\	\	\	\	\	\	\	\
	Colour of cabinet	Steel Painting	On your option	On your option	On your option	On your option	On your option	On your option	On your option	On your option
5.	Inside cabinet walls	/	Coated steel	Coated steel	Coated steel	Coated steel	Coated steel	Coated steel	Coated steel	
	Top plate		Coated steel	Coated steel	Coated steel	Coated steel	Coated steel	Coated steel	Coated steel	
	Colour of top plate		Coated steel	Coated steel	Coated steel	Coated steel	Coated steel	Coated steel	Coated steel	
	Thickness of cabinet walls	mm	40	40	40	40	40	40	40	
	Material of shelves		steel plate	steel plate	steel plate	steel plate	steel plate	steel plate	steel plate	
	Wheels/Casters/Adjustable feet	/	Adjustable feet	Adjustable feet	Adjustable feet	Adjustable feet	Adjustable feet	Adjustable feet	Adjustable feet	
	Night curtain		YES	YES	YES	YES	YES	YES	YES	
	Equipment & accessories									
	Defrost		YES	YES	YES	YES	YES	YES	YES	
	Automatic evaporation of drain water		YES	YES	YES	YES	YES	YES	YES	
6.	Shelves light	LED	LED	LED	LED	LED	LED	LED	LED	
	Number of shelves		4	4	4	4	4	4	4	
	Shelves (angle)		0°/9°/18°	0°/9°/18°	0°/9°/18°	0°/9°/18°	0°/9°/18°	0°/9°/18°	0°/9°/18°	
	Depth for shelves Glass side panel	inch (0°)	11 3/4"+13 3/4"+15 3/4"+17 3/4"	11 3/4"+13 3/4"+15 3/4"+17 3/4"	11 3/4"+13 3/4"+15 3/4"+17 3/4"	11 3/4"+13 3/4"+15 3/4"+17 3/4"	10 1/4"+11 3/4"+11 3/4"+15 3/4"	10 1/4"+11 3/4"+11 3/4"+15 3/4"	10 1/4"+11 3/4"+11 3/4"+15 3/4"	10 1/4"+11 3/4"+11 3/4"+15 3/4"
	Depth for shelves Glass side panel	mm (0°)	300+350+400+450	300+350+400+450	300+350+400+450	300+350+400+450	260+300+300+350	260+300+300+350	260+300+300+350	260+300+300+350
	Depth for shelves Foam side panel	inch (0°)	17 3/4"	17 3/4"	17 3/4"	17 3/4"	13 4/3"	13 4/3"	13 4/3"	13 4/3"
	Depth for shelves Foam side panel	mm (0°)	450	450	450	450	350	350	350	350
	Digital thermostat		YES	YES	YES	YES	YES	YES	YES	
	Solenoid valve		no	no	no	no	no	no	no	
	Evaporator fan		EBM	EBM	EBM	EBM	EBM	EBM	EBM	
7.	Evaporator		Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	
	Expansion Valve		capillary	capillary	capillary	capillary	capillary	capillary	capillary	
	condenser fan		YONGRONG	YONGRONG	YONGRONG	YONGRONG	YONGRONG	YONGRONG	YONGRONG	
	condenser		Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	Copper-aluminium fin	
	Leneth of cable	m	2.0m	2.0m	2.0m	2.0m	2.0m	2.0m	2.0m	
	Compressor		secop*1	secop*2	secop*2	secop*2	secop*1	secop*2	secop*2	
	Packing dimensions & loadability									
	Unit dimensions (W / D / H)	inch	39 1/2"X31 1/2"X78 3/4"	52"X31 1/2"X78 3/4"	60"X31 1/2"X78 3/4"	76 3/8"X31 1/2"X78 3/4"	39 1/2"X27 1/2"X78 3/4"	52"X27 1/2"X78 3/4"	60"X27 1/2"X78 3/4"	76 3/8"X27 1/2"X78 3/4"
	Unit dimensions (W / D / H)	mm	1002*800*2000	1320*800*2000	1524*800*2000	1940*800*2000	1002*700*2000	1320*700*2000	1524*700*2000	1940*700*2000
	Packing dimensions (W / D / H)(Base +frame+fumigation)	inch	44 7/8"X35"X85 7/8"	56 7/8"X35"X85 7/8"	65"X35"X85 7/8"	82"X35"X85 7/8"	44 7/8"X31 1/8"X85 7/8"	56 7/8"X31 1/8"X85 7/8"	65"X31 1/8"X85 7/8"	82"X31 1/8"X85 7/8"
Packing dimensions (W / D / H)(Base +frame+fumigation)	mm	1140*890*2180	1445*890*2180	1650*890*2180	2084*890*2180	1140*790*2180	1445*790*2180	1650*790*2180	2084*790*2180	
Packing dimensions (W / D / H)(All plywood)	inch	41 3/4"X33"X83 5/8"	54 3/8"X33"X83 5/8"	62 3/8"X33"X83 5/8"	79"X33"X83 5/8"	41 3/4"X30"X83 5/8"	54 3/8"X30"X83 5/8"	62 3/8"X30"X83 5/8"	79"X30"X83 5/8"	
Packing dimensions(W / D / H)(All plywood)	mm	1060*860*2125	1380*840*2125	1585*860*2125	2004*860*2125	1060*760*2125	1365*760*2125	1585*760*2125	2004*760*2125	