



# LEVELLINE®



## INSTALLATION INSTRUCTIONS

### LEVELLINE STICK CORNERS


When installing drywall for 90° Corners, hang drywall as shown. With a 4" (100 mm) tapping knife, apply Taping or All-Purpose joint compound to each corner at least 4" (100 mm) wide and 1/8" (3 mm) thick. To reduce installation time, use CertainTeed's Double Barrel Hopper to apply joint compound.



1. Apply LEVELLINE corner bead to the wall and press into position, ensuring that the bead is tight to the ceiling. Firmly embed corner bead using the tapping knife or Outside 90 roller. Remove any excess compound and allow to dry for 24 hours.



2. With a 6" (150 mm) tapping knife, apply a second coat of Taping or All-Purpose joint compound, carefully feathering the compound 6" (150 mm) out from the nose of the trim. Allow to dry.



3. With a 8" (200 mm) finishing knife, apply Finishing or All-Purpose joint compound to the corner as smoothly as possible, feathering out the final coat 8" (200 mm) from the nose of the trim. Allow to dry; sand and paint.

### CertainTeed Double Barrel Hopper

The Double Barrel Hopper works well with the LEVELLINE Outside 90 corner bead. Push desired length of LEVELLINE bead through hopper and install/finish as outlined earlier.

Accommodates all inside and outside angles without time-consuming part changeovers and reconfiguration.

#### Features/Benefits:

- Eliminates part changes or reconfigurations — handles both inside and outside angles.
- Single piece gates with ergonomic hand knob allow for fast and easy adjustments
- High density polyurethane tank and gate controllers
- Stainless steel reservoir trough and gates
- Dimension: 14" x 14" x 13.5"



### CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM  
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](http://certainteed.com)

USGBC® and the related logo are trademarks owned by the U.S. Green Building Council® and are used with permission.

