



www.dynamitediesel.com
 sales@dynamitediesel.com
 208.209.3214

BUILD DETAILS

SHOP NAME: _____
 CUSTOMER NAME: _____
 PO / RO: _____
 DATE: 2/15/2021
 PART NUMBER: FORD 6.7 STOCK
 NOZZLE FLOW (LPM): _____

TESTING DETAILS

TEST STAND: ARM-2
 TEST FLUID: Viscor 1487AW-2 (SAE J-967)
 FLUID TEMP: 40° C
 TECHNICIAN: _____

All flow data provided is measured in mm³ per stroke unless otherwise noted.

		INJECTOR NUMBER									
	SET POINT	1	2	3	4	5	6	7	8	AVG	VARIANCE
IDLE	25 MPA / 570 uS	3.3	3.2	3.1	4.0	4.5	5.1	4.9	4.4		2 mm ³
	120 MPA / 410 uS	21.3	21.9	21.6	21.3	21.4	21.1	21.3	21.4	21.4	
	200 MPA / 1000 uS	125.0	129.0	127.0	125.0	126.0	124.0	125.0	126.0	126.0	
	200 MPA / 1400 uS	158.2	163.2	160.7	158.2	159.4	156.9	158.2	159.4	159.4	
FULL (VL)	200 MPA / 1700 uS	172.6	178.1	175.4	172.6	174.0	171.2	172.6	174.0		
	200 MPA / 2000 uS	187.9	193.9	190.9	187.9	189.4	186.4	187.9	189.4		
	Return	24	16	13	19	21	12	10	17		

