Safety Data Sheet

DATE PREPARED 10/15/2015

STANDARD 616

6028	ORANGE	
HMIS Class	sification:	
Health		2*
Flammabilit	у	0
Reactivity		0
Personal Pi	rotection	See Section 8



UPDATED 4/13/2016

MANUFACTURERS OF CERAMIC COLORS

1.1 Product identifier

Silicic acid, zirconium salt, cadmium pigment-encapsulated Product name

Inorganic chemical materials smelted at high temperatures

Product number EC no. CAS no. Index no. 1.4 Supplier's details	6028 ORANGE 310-077-5 102184-95-2 N/A
Name Address	Mason Color Works Inc. 250 East Second Street East Livepool, Ohio 43920 USA
Telephone Fax	330 385 4400 330 385 4488

SECTION 2: Hazard Identification

Signal Word: WARNING GHS classification in accordance with OSHA (29 CFR 1910.1200) H303: May be harmful if swallowed H313: May be harmful in contact with skin H317: May cause an allergic skin reaction H333: May be harmful if inhaled H335: May cause respiratory irritation

Not a hazardous substance P261: Avoid breathing dust. P262: Do not get in eyes, on skin. P264: Wash hands thoroughly after handling.



SECTION 3: Composition/information on ingredients

Silicic acid, zirconium salt, cadmium pigment-encapsulated

EC no.	310-077-5
CAS no. Index no.	102184-95-2
	NA
Formula	unspecified

100%

CAS no.	102184-95-2
Index no.	NA
Formula	unspecified
SECTION 4: First-aid measures	
•Contact with skin:	Wash with plenty of water and soap.
•Contact with eyes:	Wash immediately with water for at least 10 minutes.
•Swallowing:	Induce vomiting. SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.
	A suspension of activated charcoal in water, or liquid paraffin may be administered.
•Inhalation:	Ventilate the premises.
	The patient is to be removed immediately from the contaminated premises and made to rest in a well ventilated area.

Should the patient feel unwell, OBTAIN MEDICAL ATTENTION

SECTION 5: Fire-fighting measures

 Recommended extinguishers: 	Water, CO2, Foam, Chemical powders, according to the materials involved in the fire.
•Extinguishers not to be used:	None in particular.
 Risks arising from combustion: 	Avoid inhaling the fumes.
•Protective equipment:	Use protection for the respiratory tract.

SECTION 6: Accidental release measures

 Measures for personal safety: 	Use gloves and protective clothing. In the event of particulates aerosols use respiratory protection.		
Environmental measures: . Keep away from drains, surface- and ground-water and soil			
•Cleaning methods: Limit leakages with earth or sand. If the product has escaped into a water			
	course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.		
	Remove the waste materials with a suitable device (for instance a suction pump) and dispose.		
	After the product has been recovered, rinse the area and materials involved with water.		

SECTION 7: Handling and storage

 Handling precautions: 	Wear suitable gloves, glasses and face protection. Avoid contact and inhalation of the vapours/powders.	
	Do not eat or drink while working.	
 Incompatible materials: 	None in particular.	
•Storage conditions:	Always keep the containers tightly closed.	
 Instructions as regards storage premises: 	Adequately ventilated premises.	

SECTION 8: Exposure controls / personal protection

Zirconium Compounds (as Zr)	ACGIH-TLVs 10 mg/m ³ (total)	OSHA PELs 15 mg/m ³ (total)	NOISHA RELs 5 mg/m ³
	5 mg/m ³ (Respirable)	5 mg/m ³ (respirable)	15 min. C
Silica, Crystalline (SiO2)	0.1 mg/m ³	10 mg/m ³	0.05 mg/m ³
Cadmium dust (as Cd)	0.01 mg/m ³	0.005 mg/m ³	
Selenium Compounds (as Se)	0.2 mg/m ³	0.2 mg/m ³	0.2 mg/m^3

 Precautionary measures: 	Give adequate ventilation to the premises where the product is stored and/or handled.
•Respiratory protection:	Use suitable respiratory protection.
•Protection for hands:	Not needed for normal use.
•Eye protection:	Not needed for normal use.
•Protection for skin:	No special precaution must be adopted for normal use.

SECTION 9: Physical and chemical properties

Appearance/form	orange/powder
Odor	None
SPECIFIC GRAVITY	n/a
рН	NA
Melting point/freezing point	>500C
Initial boiling point and boiling range	NA
Flash point	NA
Evaporation rate	NA
Flammability (solid, gas)	none
Upper/lower flammability limits	NA
Upper/lower explosive limits	NA
Vapor pressure	NA
Vapor density	NA
Relative density	NA
Solubility(ies)	insoluble
Partition coefficient: n-octanol/water	NA
Auto-ignition temperature	NA
Decomposition temperature	NA
Viscosity	NA
Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity

Chemical stability	STABLE
Possibility of hazardous reactions	WILL NOT OCCUR
Incompatible materials	NONE
Hazardous decomposition products	N/A

SECTION 11: Toxicological information

ORAL	male/female	Endpoint LD50	Effect level > 2000 mg/kg b
INHALATION	male/female	Endpoint LC50	Effect level > 5.07 mg/L air (analytical)
SKIN	NA		

NON IRRITATING TO THE SKIN

NON IRRITATING TO THE EYES

THIS PIGMENT IS NOT LISTED IN THE NATIONAL TOXICOLOGY PROGRAM (NTP) REPORT ON CARCINOGENS.

IT IS NOT LISTED AS A POTENTIAL CARCINOGEN IN THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER(IARC) MONOGRAPHS.

IT IS NOT FOUND TO BE A CARCINOGEN BY THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION(OSHA)

SECTION 12: Ecological information

ECOTOXICITY	NO DATA
DEGRADABILITY	NO DATA
MOBILITY	NO DATA
BIOACCUMULATIVE	NO DATA

SECTION 13: Disposal considerations

Disposal of the product	Contain spillage and scoop or vacuum. Avoid making dust put in appropriate container for disposal. Waste disposal method in accordance with Federal, State and Local Laws.	
Disposal of contaminated packaging	Dispose of as unused product.	
Waste treatment	MUST BE PROCESSED THROUGH IN-HOUSE TREATMENT	
Sewage disposal	AVOID CITY DRAINS	

SECTION 14: Transport information

14.1 UN Number	None
14.2 UN Proper Shipping Name	None
14.3 Transport hazard class(es)	None
14.4 Packing group	None
14.5 Environmental hazards	None
14.6 Special precautions for user	None
14.7 Transport in bulk according to Annex II of	None
MARPOL 73/78 and the IBC Code	

SECTION 15: Regulatory information

Attention all Retailers of Mason Stains

ALL retailers of this product are REQUIRED by law to supply their customers with a copy of material safety data sheet with initial purchase.

***SARA 313

This product contains certain oxides and compounds which are subject to reporting requirements of Superfund Amendment and Reauthorization Act (**SARA**) of 1986, Section 313 of the Emergency Planning and Community Right to Know Act and of 40 CRF, Part 372.

The information contained in this MSDS must be provided to every employee who is exposed to this product in any way. We recommend the user reads and understands the contents herein before using this material.

PLEASE KEEP ON FILE FOR FUTURE REFERENCE. DO NOT THROW AWAY! MSDS'S ARE REQUIRED FOR FIRST SHIPMENT, AND WILL BE SENT AGAIN WHEN REVISED UPON YOUR NEXT ORDER OF PRODUCT OR BY REQUEST.

Disclamer

SECTION 16: REFERENCE INFORMATION

CPMA CLASSIFICATION AND CHEMICAL DESCRIPTIONS OF THE COMPLEX INORGANIC COLOR PIGMENTS Fourth Edition - January 2013 Update

https://www.osha.gov/index.html

http://chem.sis.nlm.nih.gov/chemidplus

13th Report on Carcinogens on October 2, 2014. http://monographs.iarc.fr/ENG/Classification/index.php