

MATERIAL DATA SAFETY SHEET

CALCINED CHINA CLAY

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Burgess #30, Burgess #30NA, Burgess #30-P, Burgess #50, Iceberg, Icecap K, Icecap K70, Icecap KSF, Optipozz, Optiwhite, Optiwhite B, Optiwhite MX, Optiwhite P, Tisyn.

Synonyms: Calcined kaolin, Anhydrous kaolin clay

Product use: Mineral pigment

Manufacturer:

Burgess Pigment Company, 525 Beck Boulevard, P.O. Box 349, Sandersville, Georgia 31082 U.S.A.

Safety, Health & Environmental Manager- Daytime Phone 800-841-8999 or 478-552-2544

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Component(s) (chemical & common name(s)) CAS Registry No. % (Approx.)

Anhydrous aluminum silicate (Calcined kaolin) 66402-68-4 >99

Exposure Limits - See Section 8

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Short-Term (acute):

Eye Contact: Direct contact with dust may cause irritation by mechanical abrasion.

Skin Contact: Direct contact may cause irritation by mechanical abrasion.

Inhalation: Dusts may irritate the nose, throat, and respiratory tract by mechanical abrasion. Coughing, sneezing, and shortness of breath may occur following exposures in excess of appropriate limits.

Ingestion: Expected to be practically non-toxic. Ingestion of large amounts may cause gastrointestinal irritation and blockage.

POTENTIAL HEALTH EFFECTS

Long-Term (chronic):

Calcined kaolin is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA).

Prolonged and repeated inhalation of respirable dust in excess of appropriate exposure limits has caused pneumoconiosis, a lung disease. Not all individuals with pneumoconiosis will exhibit symptoms (signs) of the disease. However, pneumoconiosis can be progressive and symptoms can appear at any time, even years after the exposure has ceased. Symptoms of pneumoconiosis may include but are not limited to the following: shortness of breath; difficulty breathing with or without exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume.

SECTION 4 - FIRST AID MEASURES

Eyes: Immediately flush eye(s) with plenty of clean water for at least 15 minutes, while holding the eyelid(s) open. Occasionally lift the eyelid(s) to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Contact a physician if irritation persists or later develops.

Skin: Wash with soap and water. Contact a physician if irritation persists or later develops.

SECTION 4 - FIRST AID MEASURES (continued)

Ingestion: If person is conscious, give large quantity of water and induce vomiting; however, never attempt to make an unconscious person drink or vomit. Get immediate medical attention.

Inhalation: Remove to fresh air. Dust in the throat and nasal passages should clear spontaneously. Contact a physician if irritation persists or later develops.

SECTION 5 - FIRE FIGHTING MEASURES

Physical Hazard: Non-combustible **Flammable Limits In Air:** Not flammable

Flashpoint: Not flammable **Autoignition Temperature:** Not flammable

Extinguishing Agents: None required **Explosion Data:** Non-explosive

Unusual Fire And Explosion Hazards: None known **Sensitivity to Static**

Discharge: Not applicable

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Care should be taken to avoid dusting while sweeping up spilled product. Cleanup personnel should use appropriate NIOSH/MSHA approved respirators if exposures are expected above the limits listed in Section 8. Water should be used with great care as it creates a slipping hazard when mixed with this product. This product is generally non-toxic to aquatic systems but may cause high turbidity in stormwater.

No components in this product are subject to the reporting requirements of Title III of SARA, 1986, and 40 CFR 372.

SECTION 7 - HANDLING AND STORAGE

Handling: Appropriate personal protection should be used when handling (refer to Section 8).

Use care when dispensing to avoid dust generation. Fold and flatten empty bags carefully to reduce dust generation.

Wash hands thoroughly after handling.

Storage: Best if kept under dry conditions. Not generally affected by hot or cold storage

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

No exposure limits have been published for calcined kaolin products. We recommend using the limits published for kaolin (cas# 1332-58-7)

Exposure Limits: Value Limit Reference

Kaolin 2 mg/m³ (Respirable dust) TWA (8 hour) ACGIH TLV-A4*
1332-58-7

15 mg/m³ (Total dust) TWA (8 hour) OSHA PEL

5 mg/m³ (Respirable dust) TWA (8 hour) OSHA PEL

10 mg/m³ (Total dust) TWA (10 hour) NIOSH REL

5 mg/m³ (Respirable dust) TWA (10 hour) NIOSH REL

Notes- (-A4) This indicates that kaolin is "Not Classifiable as a Human Carcinogen" by ACGIH.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Engineering Controls: Respirable dust levels should be monitored regularly. Dust levels in excess of appropriate exposure limits should be reduced by all feasible engineering controls, including (but not limited to) wet suppression, ventilation, process enclosure, and enclosed employee work stations.

Respiratory Protection: For respirable dust levels that exceed or are likely to exceed and 8hr-TWA of 2 mg/m³, a NIOSH/MSHA approved HEPA filter respirator must be worn. Respirator use must comply with applicable MSHA or OSHA standards which include provisions for a user training program, respirator repair and cleaning, respirator fit testing and other requirements.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: N/A (Solid) **Specific Gravity (H₂O=1):** 2.2- 2.6 depending on

product

Vapor Pressure (mm Hg): No Vapor **Melting Point:** >1700° C

Vapor Density (Air=1): No Vapor **Appearance and Odor:** Off-white dry powder

Solubility in Water: Insoluble **pH in Water (20% solids suspension):** 4.0- 6.3

SECTION 10 - STABILITY AND REACTIVITY

Stability: This product is stable under normal storage conditions.

Hazardous Polymerization: Will not occur under normal conditions.

Incompatibility With Other Materials: None known

Hazardous Decomposition Products: None known

SECTION 11 - TOXICOLOGICAL Information

Calcined kaolin is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). The American Conference of Governmental Industrial Hygienists (ACGIH) lists kaolin as- Not Classifiable as a Human Carcinogen: Inadequate data on which to classify the agent in terms of its carcinogenicity in humans and/or animals.

SECTION 12 - ECOLOGICAL INFORMATION

Ecological Information: No adverse ecological effects are expected. May affect turbidity of water if discharged in large quantities to lakes or streams.

SECTION 13 - DISPOSAL CONSIDERATIONS

Pickup and reuse clean materials, avoiding dusting situations. Dispose of waste materials only in accordance with applicable federal, state, and local laws and regulations. This product is not hazardous as a waste. Check with local landfills before disposing in trash. Dispose of in closed containers to avoid dusting.

SECTION 14 - TRANSPORTATION INFORMATION

DOT Hazard Classification: None

Placard Required: None

Label Required: Use original label including all warnings. When disposing of this material in its pure form use a DOT "Non-Hazardous Waste" label.

SECTION 15 - REGULATORY INFORMATION

U.S. Federal Regulations

OSHA: This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200)

SARA Section 311/312: This product does not contain any hazardous components subject to the reporting requirements of Section 311 or 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 370.

SARA Section 313: This product contains no substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

TSCA: This product or its components are listed in or exempt from the TSCA inventory requirements. This product contains no substances subject to export notification under Section 12(b) of TSCA.

State Regulations

Several states specifically list kaolin and regulate dust exposure. For the most current regulatory information please contact the appropriate agencies in the state where the product is to be handled. Kaolin is known to be listed in the following states: Alaska, Arizona, California, Idaho, Indiana, Massachusetts, Michigan, North Carolina, Oregon, Pennsylvania, Tennessee, Texas, Vermont, and Washington.


Foreign Regulations: Kaolin clay (CAS # 1332-58-7) can be found in the following registries: DSL (Canada), ENCS (Japan), ECL (Korea), AICS (Australia), SWISS (Swiss), PICCS (Philippines), HSNO (New Zealand), China. Kaolinite (CAS # 1318-74-7) can be found in the following registries: NDSL (Canada), EINECS (Europe), ECL (Korea).

R phrases: R36/37, R66 S phrases: S24/25, S37/39, S38

The German Ministry of the Environment considers this product not dangerous to water.

SECTION 16 - OTHER INFORMATION

Calcined kaolin is a man-made product with the following chemical formula -



Hazard Communication or "Right-to-know" information-

Hazardous Materials Identification System (HMIS[®]) Ratings:

Health = 0* Potential chronic effects

Reactivity = 0 Non-reactive

Flammability = 0 Non-flammable

Personal Protection Equipment = E**

*Prolonged breathing of excessive dust may adversely affect lung function.

**Use NIOSH approved dust mask for dusty conditions.

This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Burgess Pigment Company

525 Beck Blvd.

Sandersville, GA 31082

(478) 552-2544

(800) 841-8999

Fax (478) 552-4274

Email - info@burgesspigment.com