

SAFETY DATA SHEET

Section 1. Identification

Product identifier : BAYFERROX 3910
Material Number : 00005851
Identified uses : Inorganic pigment
Supplier/Manufacturer : LANXESS Corporation
Product Safety & Regulatory Affairs
111 RIDC Park West Drive
Pittsburgh, PA 15275-1112
USA

For information: US/Canada (800) LANXESS
International +1 412 809 1000

In case of emergency : Chemtrec (800) 424-9300
International (703) 527-3887
Lanxess Emergency Phone (800) 410-3063.

Section 2. Hazards identification

HAZCOM Standard Status : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), the SDS contains valuable information critical to the safe handling and proper use of the product. The SDS should be retained and available for employees and other users of this product.

Physical state : Powder.
Color : Yellow.
Classification of the substance or mixture : Not classified.
Signal word : No signal word.
Hazard statements : No known significant effects or critical hazards.
Hazard Not Otherwise Classified (HNOC) : None known.
Precautionary statements
Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.
Supplemental label elements : Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Titanium dioxide (Rutile)	5 - 10%	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Potential acute health effects

- Eye contact** : May cause mechanical irritation (abrasion).
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause mechanical irritation (abrasion).
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Potential chronic health effects

No known significant effects or critical hazards.

Notes to physician : Treat symptomatically. No specific treatment.

Protection of first-aiders : No special measures required.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire. In case of fire, use water spray (fog), foam or dry chemical.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : No specific fire or explosion hazard.

Hazardous thermal decomposition products : No specific data.

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing dust. Put on appropriate personal protective equipment.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods and materials for containment and cleaning up** : Move containers from spill area. Approach release from upwind. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. Prevent entry into sewers, water courses, basements or confined areas.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Avoid breathing dust. Remove contaminated clothing and protective equipment before entering eating areas. Workers should wash hands and face before eating, drinking and smoking. Put on appropriate personal protection equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
- Conditions for safe storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Empty containers or liners may retain some product residues.

Section 8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide (Rutile)	ACGIH TLV (United States, 6/2013). TWA: 10 mg/m ³ 8 hours. OSHA PEL (United States, 2/2013). TWA: 15 mg/m ³ 8 hours. Form: Total dust

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

- Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Dust-protection mask
- Skin protection** : Wear suitable protective clothing and gloves. Suitable protective footwear.
- Eye/face protection** : If contact with product is possible, wear safety glasses with side shields.

Section 8. Exposure controls/personal protection

Medical Surveillance : Not available.

Section 9. Physical and chemical properties

Physical state : Solid. [powders]
Color : Yellow.
Odor : Odorless.
Odor threshold : Not available.
pH : 4.5 to 7.5 [Conc. (% w/w): 50%]
Boiling point : Not available.
Melting point : >1000°C (>1832°F)
Flash point : Not available.
Evaporation rate : Not available.
Explosion limits : Not available.
Vapor pressure : Not available.
Density : 4 g/cm³
Specific gravity (Relative density) : Not available.
Solubility : Insoluble in the following materials: cold water
Partition coefficient: n-octanol/water : Not available.
Vapor density : Not available.
Viscosity : Not available.
Auto-ignition temperature : Not available.
Decomposition temperature : 180°C

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.
Chemical stability : The product is stable.
Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid : Excessive temperatures. At temperatures greater than 176 F (80 C), this product may become unstable and slowly auto-oxidize into Fe₂O₃ which generates additional heat. Under certain conditions this heat may be sufficient to cause combustible materials to ignite.
Incompatible materials : No specific data.
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on the likely routes of exposure : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eye contact : May cause mechanical irritation (abrasion).
Inhalation : No known significant effects or critical hazards.
Skin contact : May cause mechanical irritation (abrasion).
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.

Section 11. Toxicological information

Ingestion : No specific data.

Potential chronic health effects

Short term exposure

Potential immediate effects : Not available.

Long term exposure

Potential delayed effects : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	Test
BAYFERROX 3910 PIGMENT	LD50 Oral	Rat	>15000 mg/kg	-	-
Titanium dioxide (Rutile)	LC50 Inhalation Dusts and mists	Rat	>6.82 g/m ³	4 hours	*

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide (Rutile)	Skin - Erythema/Eschar	Rabbit	0.28	-	-
	Skin - Edema	Rabbit	0	-	-
	Eyes - Edema of the conjunctivae	Rabbit	0	-	-
	Eyes - Redness of the conjunctivae	Rabbit	0.1	-	-

Conclusion/Summary

Skin : Non-irritating. *Test results on an analogous product

Eyes : Non-irritating. *Test results on an analogous product

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Titanium dioxide (Rutile)	skin	Guinea pig	Not sensitizing
	skin	Mouse	Not sensitizing

Conclusion/Summary

Chronic toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium dioxide (Rutile)	Sub-chronic NOEL Oral	Rat - Male	24000 mg/kg	29 days; 7 days per week
	Chronic NOEL Inhalation Dusts and mists	Rat - Male, Female	10 mg/m ³	2 years; 6 hours per day

Mutagenicity

Section 11. Toxicological information

Product/ingredient name	Test	Experiment	Result
Titanium dioxide (Rutile)	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	OECD 473 <i>In vitro</i> Mammalian Chromosomal Aberration Test	Experiment: In vitro Subject: Mammalian-Animal Cell: Germ	Negative
	OECD 476 <i>In vitro</i> Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic	Negative
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vitro Subject: Mammalian-Animal Cell: Germ	Negative
	OECD 487 <i>In vitro</i> Micronucleus Test	Experiment: In vitro Subject: Mammalian-Human Cell: Somatic	Negative

Conclusion/Summary : Titanium dioxide (Rutile):Not mutagenic in a standard battery of genetic toxicological tests.

Carcinogenicity

Conclusion/Summary : In a lifetime inhalation study rats were exposed for 2 years to respirable TiO₂. Microscopic lung tumors were observed in some rats which caused overloading and impairment of rat lung clearance mechanisms. Mice and hamsters did not develop lung tumors under similar testing conditions.

Detailed epidemiology studies have also shown no causative link between titanium dioxide exposure and cancer risk in human and no lung cancer hazard workplace exposure concentration. In February 2006 IARC concluded, "There is inadequate evidence in humans for the carcinogenicity of titanium dioxide."

Product/ingredient name	CAS #	IARC	NTP	OSHA
Titanium dioxide (Rutile)	13463-67-7	2B Possibly carcinogenic to humans	Not classified.	Not classified.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Titanium dioxide (Rutile)	Category 3	Not applicable.	Respiratory tract irritation

Acute toxicity estimates

Route	ATE value (Acute Toxicity Estimates)
Not available.	

Section 12. Ecological information

Toxicity

Section 12. Ecological information

Product/ingredient name	Test	Result	Species	Exposure
Titanium dioxide (Rutile)	OECD 202 <i>Daphnia</i> sp. Acute Immobilization Test	Acute EC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	-	Acute IC50 61 mg/l Growth rate inhibition	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours
	EPA 540/9-85-006	Acute LC50 >1000 mg/l Fresh water	Fish - <i>Pimephales promelas</i>	96 hours
	OECD 209 Activated Sludge, Respiration Inhibition Test	Chronic EC50 >1000 mg/l Fresh water	Bacteria	3 hours
	-	Chronic IC10 12.7 mg/l Growth rate inhibition	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Titanium dioxide (Rutile)	-	<400	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Waste disposal should be in accordance with existing federal state, provincial and or local environmental controls laws.

RCRA classification : If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR 261.20-24)

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	-	-	-	-		Not regulated.
IMDG Class	-	-	-	-		Not regulated.
IATA-DGR Class	-	-	-	-		Not regulated.

PG* : Packing group

RQ : 0 lbs

Section 15. Regulatory information

SARA 311/312 : Not applicable.

SARA Title III Section 302 : None
Extremely Hazardous Substances

SARA Title III Section 313 : None
Toxic Chemicals

US EPA CERCLA : None
Hazardous Substances (40 CFR 302)

State regulations

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections on the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

<u>Ingredient name</u>	<u>CAS number</u>	<u>State Code</u>	<u>Concentration (%)</u>
Titanium dioxide (Rutile)	13463-67-7	MA - S, NJ - HS, PA - RTK HS	5 - 10%
C.I. Pigment Yellow 42	51274-00-1		91 - 97%

Massachusetts Substances: MA - S

Massachusetts Extraordinary Hazardous Substances: MA - Extra HS

New Jersey Hazardous Substances: NJ - HS

Pennsylvania RTK Hazardous Substances: PA - RTK HS

Pennsylvania Special Hazardous Substances: PA - Special HS

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Potential exposure to some or all of the California Proposition 65 chemicals in this product have been determined to be below the No Significant Risk Level (NSRL)

<u>Ingredient name</u>	<u>CAS #</u>	<u>Concentration (%)</u>	<u>Cancer</u>	<u>Reproductive</u>
Titanium dioxide (Rutile)	13463-67-7	5 - 10%	Yes	

U.S. Toxic Substances Control Act : Listed on the TSCA Inventory.

Section 16. Other information

Hazardous Material Information System :

Health	1
Flammability	0
Physical hazards	0

0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme
*=Chronic

The customer is responsible for determining the PPE code for this material. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

National Fire Protection Association (U.S.A.) :



Section 16. Other information

0= Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

LANXESS' method of hazard communication is comprised of Product Labels and Safety Data Sheets. HMIS and NFPA ratings are provided by LANXESS as a customer service.

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Date of issue : 08-05-2014

Date of previous issue : 08-05-2014

Version : 2

Product Safety and Regulatory Affairs

Indicates information that has changed from previously issued version.

Notice to reader

This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of LANXESS Corporation. The information in this SDS relates only to the specific material designated herein. LANXESS Corporation assumes no legal responsibility for use of or reliance upon the information in this SDS.