

## 1 Identification

**Product identifier**

**Trade name:** *V 18 THINNINGOIL*

**Article number:** 88040008

**Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture**

Decoration materials or decoration aids for glass or porcelain ware.

**Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**

Heraeus Precious Metals GmbH & Co. KG

Heraeusstr. 12-14

D-63450 Hanau

**Information department:**

Electronic Materials Division

Telefon: 0049 6181-35 4217

Telefax: 0049 6181-35 16 4217

Mail: [tfd-msds@heraeus.com](mailto:tfd-msds@heraeus.com)

**Emergency telephone number:**

24-h-Number:

0049 6132-84463

## 2 Composition/information on ingredients

**Chemical characterization: Mixtures**

**Description:** Chemical Mixture

**Dangerous components:**

8006-64-2	Turpentine, oil	50-75%
108-88-3	toluene	10-25%
8000-25-7	Rosemary oil	5-10%
111-90-0	2-(2-ethoxyethoxy)ethanol	≤ 2.5%
78-70-6	Linalool	≤ 1.0%
7785-26-4	(-)-pin-2(3)-ene	≤ 1.0%
68526-86-3	Alcohols, C11-14-iso-, C13-rich	≤ 1.0%
138-86-3	dipentene	≤ 0.5%
106-24-1	Geraniol	≤ 0.5%

## 3 Hazard(s) identification

**Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Trade name: V 18 THINNINGOIL

(Contd. of page 1)



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.  
 Acute Tox. 4 H332 Harmful if inhaled.  
 Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 Skin Sens. 1 H317 May cause an allergic skin reaction.

**Label elements**

**GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms**



GHS02

GHS07

GHS08

**Signal word Danger**

**Hazard-determining components of labeling:**

Turpentine, oil  
 toluene  
 Linalool  
 dipentene  
 Geraniol

**Hazard statements**


H226 Flammable liquid and vapour.  
 H312+H332 Harmful in contact with skin or if inhaled.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H317 May cause an allergic skin reaction.  
 H361 Suspected of damaging fertility or the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H304 May be fatal if swallowed and enters airways.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read label before use.  
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:**

**NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)

Trade name: V 18 THINNINGOIL

- HMIS-ratings (scale 0 - 4)

HEALTH	2
FIRE	3
REACTIVITY	0

Health = \*2

Fire = 3

Reactivity = 0

(Contd. of page 2)

#### 4 First-aid measures

• **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

• **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:** Immediately call a doctor.

#### 5 Fire-fighting measures

• **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

• **For safety reasons unsuitable extinguishing agents:**

Water

Water with full jet

• **Special hazards arising from the substance or mixture** No further relevant information available.

• **Protective equipment:** Mount respiratory protective device.

#### 6 Accidental release measures

• **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective clothing.

• **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

• **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

• **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

(Contd. on page 4)

Trade name: V 18 THINNINGOIL

(Contd. of page 3)

**Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**Storage:**

- Requirements to be met by storerooms and receptacles: No special requirements
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:  
Keep receptacle tightly sealed.  
Prevent from drying out.
- Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

**Components with limit values that require monitoring at the workplace:**

**8006-64-2 Turpentine, oil**

PEL ()	Long-term value: 560 mg/m <sup>3</sup> , 100 ppm
REL ()	Long-term value: 560 mg/m <sup>3</sup> , 100 ppm
TLV ()	Long-term value: 112 mg/m <sup>3</sup> , 20 ppm (SEN) NIC-DSEN

**108-88-3 toluene**

PEL ()	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL ()	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV ()	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

**111-90-0 2-(2-ethoxyethoxy)ethanol**

WEEL ()	Long-term value: 25 ppm
---------	-------------------------

**138-86-3 dipentene**

WEEL ()	Long-term value: 30 ppm
---------	-------------------------

**Ingredients with biological limit values:**

**108-88-3 toluene**

BEI ()	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

Additional information: The lists that were valid during the creation were used as basis.

**Personal protective equipment:**

**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)

Trade name: V 18 THINNINGOIL

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

**Breathing equipment:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2B2P3

**Protection of hands:**



Protective gloves

Only use chemical-protective gloves with CE-labeling of category III.

Check protective gloves prior to each use for their proper condition.

After use of gloves apply skin-cleaning agents and skin cosmetics.

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

For short use and minimal soiling we recommend disposable protective gloves made of special nitrile.

For longer use and stronger soiling we recommend 4H-Chemicals-Protective-Gloves from the company SETON.

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Tightly sealed goggles

**Body protection: Protective work clothing**

### 9 Physical and chemical properties

**General Information**

**Appearance:**

Form:	Fluid
Color:	Colorless
Odor:	Characteristic
Odour threshold:	Not determined.

pH-value: Not determined.

**Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

Flash point: < 55 °C (< 131 °F)

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 220 °C (428 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 6)

**Trade name: V 18 THINNINGOIL**

(Contd. of page 5)

<b>Explosion limits:</b>	
Lower:	0.8 Vol %
Upper:	7.0 Vol %
<b>Vapor pressure at 20 °C (68 °F):</b> 29 hPa (22 mm Hg)	
<b>Density:</b> Not determined.	
<b>Relative density:</b> Not determined.	
<b>Vapour density:</b> Not determined.	
<b>Evaporation rate:</b> Not determined.	
<b>Solubility in / Miscibility with Water at 20 °C (68 °F):</b> 0.02 g/l	
<b>Partition coefficient (n-octanol/water):</b> Not determined.	
<b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
<b>Solvent content:</b>	
Organic solvents:	80 - 90 %
Water:	0.0 %
<b>Solids content:</b> 0.0 %	
<b>Other information:</b> No further relevant information available.	

### 10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.  
( < 100 °C )
- Incompatible materials:** No further relevant information available.
- Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- Acute toxicity:**
- LD/LC50 values that are relevant for classification:**

**8006-64-2 Turpentine, oil**

Oral	LD50	5760 mg/kg (rat)
------	------	------------------

**108-88-3 toluene**

Oral	LD50	636 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rbt)
Inhalative	LC50/4 h	28.1 mg/l (rat)

**111-90-0 2-(2-ethoxyethoxy)ethanol**

Oral	LD50	5500 mg/kg (rat)
Dermal	LD50	8500 mg/kg (rbt)

**78-70-6 Linalool**

Oral	LD50	2790 mg/kg (rat)
Dermal	LD50	5610 mg/kg (rbt)

**7785-26-4 (-)-pin-2(3)-ene**

Oral	LD50	3700 mg/kg (rat)
------	------	------------------

(Contd. on page 7)

Trade name: V 18 THINNINGOIL

(Contd. of page 6)

### 138-86-3 dipentene

Oral	LD50	5300 mg/kg (rat) (RTECS)
Dermal	LD50	> 2000 mg/kg (kan)

- **Primary irritant effect:**
  - *on the skin:* Irritant to skin and mucous membranes.
  - *on the eye:* Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
- **Carcinogenic categories**

#### - IARC (International Agency for Research on Cancer)

108-88-3 toluene	3
------------------	---

#### - NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

### - Aquatic toxicity:

#### 8006-64-2 Turpentine, oil

EC50	14.1 mg/l (daphnia)
------	---------------------

#### 108-88-3 toluene

EC50/30min	20 mg/l (bak)
EC50/48h	6 mg/l (daphnia)
IC50/72h	12 mg/l (algae)
LC50/96h	5.8 mg/l (fish)

#### 138-86-3 dipentene

EC50/48h	17 mg/l (daphnia) (ECOTOX Database)
LC50/96h	80 mg/l (fish) (Regenbogenforelle, ECOTOX Database)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
  - Water hazard class 2 (in accordance with VwVwS from 15.05.1999); hazardous for water
  - Do not allow product to reach ground water, water course or sewage system.
  - Danger to drinking water if even small quantities leak into the ground.
  - Also poisonous for fish and plankton in water bodies.
  - Toxic for aquatic organisms

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
  - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
  - Contact manufacturer for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 8)

Printing date 01/06/2014

Version number 9

Reviewed on 01/06/2014

**Trade name: V 18 THINNINGOIL**

(Contd. of page 7)

### 14 Transport information

· UN-Number	UN1263
· DOT, ADR, IMDG, IATA	
· UN proper shipping name	Paint
· DOT	1263 Paint, special provision 640E, ENVIRONMENTALLY HAZARDOUS
· ADR	PAINT (TURPENTINE, Rosemary oil), MARINE POLLUTANT
· IMDG	PAINT
· IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids.
· Label	3
· ADR, IMDG	
 	
· Class	3 Flammable liquids
· Label	3
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	III
· DOT, ADR, IMDG, IATA	
· Environmental hazards:	Product contains environmentally hazardous substances: Alcohols, C11-14-iso-, C13-rich, Turpentine, oil
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E,S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN1263, Paint, special provision 640E, ENVIRONMENTALLY HAZARDOUS, 3, III

(Contd. on page 9)



Trade name: V 18 THINNINGOIL

(Contd. of page 8)

**15 Regulatory information**

**Sara**

**Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

**Section 313 (Specific toxic chemical listings):**

108-88-3 toluene

**TSCA (Toxic Substances Control Act):**

All ingredients are listed.

**Proposition 65**

**Chemicals known to cause cancer:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity for females:**

108-88-3 toluene

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**Chemicals known to cause developmental toxicity:**

108-88-3 toluene

**Carcinogeny categories**

**EPA (Environmental Protection Agency)**

108-88-3 toluene

II

**TLV (Threshold Limit Value established by ACGIH)**

108-88-3 toluene

A4

**NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms**



GHS02 GHS07 GHS08

**Signal word** Danger

**Hazard-determining components of labeling:**

Turpentine, oil

toluene

Linalool

dipentene

Geraniol

**Hazard statements**

H226 Flammable liquid and vapour.

H312-H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 10)

**Trade name: V 18 THINNINGOIL**

(Contd. of page 9)

**H304** May be fatal if swallowed and enters airways.**Precautionary statements****P101** If medical advice is needed, have product container or label at hand.**P102** Keep out of reach of children.**P103** Read label before use.**P210** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**P301+P310** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.**P303+P361+P353** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P405** Store locked up.**P501** Dispose of contents/container in accordance with local/regional/national/international regulations.**Information about limitation of use:**

Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS:** TFD-MSDS- **Contact:** Mr. Hesse- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(calc.): calculated

- \* **Data compared to the previous version altered.**