

SAFETY DATA SHEET

Section 1: IDENTIFICATION

Name, address, telephone number and emergency telephone number of the manufacturer:

Standard Ceramic Supply Company 24 Chestnut Street / P.O. Box 16240 Carnegie, PA 15106-2028

Telephone / Emergency Telephone Number: 412-276-6333

Product Identifier used on the label: Lead-Free Low Fire Glazes

Recommended use of product: Glazing of ceramic ware

Canary Yellow (Glossy)	NL3
Maroon (Glossy)	NL10
Cinnamon (Glossy)	NL13
Dark Brown (Glossy)	NL15
Eggplant (Glossy)	NL19
Midnight Blue (Glossy)	NL20
Twilight Blue (Glossy)	NL23
Apple Green (Glossy)	NL27
Opaque White (Glossy)	NL31
Jet Black (Glossy)	NL35
Transparent (Glossy)	NL36
Hunter Green (Glossy)	NL37
Red Orange (Glossy)	NL55
Dark Red (Glossy)	NL56
Bright Orange (Glossy)	NL57
Ultra Clear (Glossy)	NL79



Section 2: HAZARDS IDENTIFICATION

Contains Crystalline Silica

Classification:

Eye Damage/Irritation

Skin Corrosion/Irritation

Toxicity - Single Exposure

Category 2

Category 2Specific Target Organ

Category 3 - Respiratory

Specific Target Organ Toxicity/Repeated Exposure Category 1 - Respiratory Carcinogenicity

Category 1a

Label Elements:



Signal Word:

DANGER

Hazard Statement(s): H872: Causes damage to lungs through prolonged or repeated inhalation.

Precautionary Statement(s): P260: Do not breathe dust.

P285: In case of inadequate ventilation wear respiratory protection.

P501: Dispose of contents/containers in accordance with local regulation.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	% OF FORMULA
Frit (lead free)	65997-18-4	0% - 90%
Various Pigments	Confidential	0% - 15%
Kaolin/Clay	1332-58-7	0% - 15%
Zinc Oxide	1314-13-2	0% - 10%
Zirconium Silicate (Zr Si 04)	10101-57-7	0% - 15%
Bentonite	1302-78-9	0% - 2%



Section 4: FIRST-AID MEASURES

DESCRIPTION OF FIRST-AID MEASURES

Ingestion: Contact a physician immediately.

Inhalation: May cause irritation; remove from exposure.

Skin Contact: May cause irritation; rinse skin with soap and water.

Eye Contact: May cause irritation; flush eyes with water for at least 15 minutes. If irritation

continues afterwards, contact a physician.

Section 5: FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Suitable extinguishing media: None

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS

Protective equipment for firefighters: None

Special firefighting procedures: None

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and/or Emergency Procedures: None

Environmental Precautions: None

Methods and Materials for Containment and Clean Up: None

Special Spill Response Procedures: None

Section 7: HANDLING AND STORAGE

Precautions for Safe Handling and Use: Local Exhaust Ventilation when spraying

Conditions for Safe Storage: None

Incompatible Materials: None

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS



Ingredients	OSHA PEL	ACGIH TLV
Frit (lead free)	N/A	N/A
Various Pigments	N/A	N/A
Kaolin/Clay	N/A	N/A
Zinc Oxide	15mg/m3	2mg/m3
Zirconium Silicate	N/A	N/A
Bentonite	30mg/m3	0.1mg/m3

EXPOSURE CONTROLS

Ventilation and engineering measures: Adequate Ventilation (local exhaust) when spraying.

Respiratory protection: Use a NIOSH approved respirator when spraying.

Skin protection: Wear appropriate protective clothing such as, overalls, smocks, and aprons.

Eye/face protection: Wear safety glasses to keep dust out of your eyes.

Hygienic Practices: Food, beverages, and smoking materials should not be in work area. Employees should wash hands thoroughly before eating, drinking, or smoking.

Section 9: PHYSICAL/CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):

Colored or clear liquids

Upper/lower flammability or explosive limits:

None

Odor:

None N/A

Vapor pressure: Odor threshold:

. . , . .


Negligible

Vapor density:

N/A

рН:

N/A





Relative density:

N/A

Freezing point:

32 degrees Fahrenheit

Solubility(ies)

N/A

Initial boiling point and boiling range:

N/A

Flash Point:

N/A

Evaporation rate:

N/A

Flammability (solid gas)

Partition coefficient: n-octanol/water:

N/A

None

Auto-ignition temperature:

N/A

Decomposition temperature:

None

Viscosity:

N/A

Section 10 : STABILITY / REACTIVITY

Reactivity: N/A

Chemical stability: Stable

Possibility of hazardous reactions: None

Conditions to avoid: Fumes from firing in the kiln; Mist created from applying spray

Incompatible materials: None

Hazardous decomposition products: N/A

Section 11: TOXICOLGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE

Routes of Entry: Inhalation is the most important during dispensing and mixing of dry products or excessive handling of unfired glazed materials during spraying.

POTENTIAL HEALTH EFFECTS, Signs and symptoms of short-term (acute) exposure:

Sign and symptoms inhalation: Coughing or irritation may occur.

Sign and symptoms ingestion: Sickness or irritation may occur.



Sign and symptoms skin: Redness or irritation may occur.

Sign and symptoms eyes: Redness or irritation may occur.

Potential chronic health effects: These mixtures contain silica, which can cause Silicosis through inhalation over an extended period of time. Overexposure to silica may also result in injury to the lungs.

Carcinogenicity: Cobalt is considered an animal carcinogen. Silica (quartz) is a human carcinogen.

Additional Information: The water-based, premixed products and the dry mix products, when mixed with water, should be non-toxic during recommended use.

Pigments are various metals and compound metals. The risk of exposure to these metals is minimal due to low percentages used in glazed formulas. Dermal exposure is negligible sine metals have poor dermal absorption. Inhalation exposure increases with the use of dry mix products.

Frits are fused silica glass like substances. Bioavailability is limited because of the physical appearance of the frit.

Toxicological data: These products conform to ASTM-4236 and have been certified by an independent, 3rd party toxicologist to be NON-TOXIC.

Section 12: ECOLOGICAL INFORMATION (non-mandatory)

Eco toxicity: None

Persistence and degradability: Yes

Bioaccumulation potential: No

Mobility in soil: No

Other adverse environmental effects: None

Section 13: DISPOSAL CONSIDERATIONS (non-mandatory)

Handling for Disposal: None

Methods of Disposal: None



Section 14: TRANSPORT INFORMATION (non-mandatory)

UN Shipping Name: N/A

UN Number: None

Environmental Hazard: None

Packing Group: None

Transportation Hazard Class: N/A

Special Precautions: None

NOT DANGEROUS FOR TRANSPORT

Section 15: REGULATORY INFORMATION (non-mandatory)

Silica (Quartz) and Cobalt are both listed by California, Proposition 65, as a carcinogen.

Silica (Quartz) and Cobalt are listed on the IARC, OSHA, and NTP carcinogen list.

All ingredients are on U.S. TSCA Inventory.

All products listed in this SDS conform to ASTM-4236 standards. Materials have been evaluated under the provisions of Labeling of Hazardous Art Material Act. These products have been listed as non-toxic and non-flammable under proposed conditions. No specific warning is required.

Section 16: OTHER INFORMATION

This information is furnished without warranty, representation, inducement, or license of any kind, except that it is accurate to the best of knowledge of Standard Ceramic Supply Company or obtained from other references and sources believed to be accurate.

Standard Ceramic Supply Company does not assume any legal responsibility for use or reliance on our products. Customers are encouraged to conduct their own tests before using any product. Read all product labels prior to handling.

Preparation date: 05/20/2014