

Pallet Truck



TSC



SPECIFICATIONS

- Specially designed to lift and transport the widest variety of loads in stores and warehouse.
- The ergonomic tiller safely protects the operator's hands while working.
- Excellent hydraulic lift unit.
- Strong, torsion-resistant steel construction.
- Load-in/load-out rollers under the fork tips enable pallets to be entered any kind of pallet.
- No routine maintenance at all is needed on the hydraulics unit and bearings.
- Important seals made in Germany, which prolong the working time of hydraulic unit.
- With different options for fork width and length.
- With options for Nylon, Rubber wheel and PU wheels.

Pallet Truck



1. Load roller tandem wheel 2. Load roller single wheel 3. Handle 4. Polyurethane wheel 5. Nylon wheel 6. Hydraulic pump

SPECIFICATION	TSC-2.5N	TSC-2.5NT	TSC-3NT	TSC-3
Lifting capacity	2.5 ton	2.5 ton	3 ton	3 ton
Lowered fork height H1	8.5 cm	7.5 cm	7.5 cm	7.5 cm
Total lift height H2	20 cm	19 cm	19 cm	19 cm
Fork length L1	122 cm	122 cm	122 cm	122 cm
Fork width over the forks B	68.5 cm	68.5 cm	68.5 cm	68.5 cm
Steering wheel A	Φ20x5 cm	Φ18x5 cm	Φ18x5 cm	Φ18x5 cm
Load roller single	Φ8x9.3 cm	N/A	N/A	N/A
Load roller tandem	N/A	Φ7.4x7 cm	Φ7.4x7 cm	Φ7.4x7 cm
Self weight	90 kg	92 kg	92 kg	92 kg

Pallet Truck



Size Parameters

