



AVALON WALL MOUNTED

CODE: BCNSS

NOTE: Height and reach can be adjusted to suit design requirements.

SHOWER ROSE:

Reach 450mm (centre to centre), adjustable 300mm to 700mm.

Natura 200mm diameter (as shown)

Rose height 2100mm

Daintree 250mm diameter (not shown)

Daintree 200mm diameter (available mid-2021)

Rose height 2070mm

SHOWER PIPE:

32mm dia (25mm dia by request)

Total length 1900mm

Overall depth including taps 155mm

Tap centre height 1000mm

Tap spacing 280mm, customisable down to a minimum of 170mm

Customisable with footwash on request

TAPS: Brooklyn Fire Wall Taps.

Jumper Valve taps. Also available with Brooklyn Cross Wall Taps. In wall bodies to be recessed 5-10mm from finished wall.

ROUGH IN: Requires half inch male threaded connection point (19BP) at 200mm below desired shower rose height (2m is recommended height for shower rose).

PLEASE NOTE: For timber framed walls, timber block required on centre line of shower from 500mm to 1m off FFL.

WELS:

Avalon Wall unit with Bundeena shower (Code BCCBS) Flow Rate: 9L/min.

3 Star rating WELS registration #SM13610

Avalon Wall unit with Eden shower (Code BCCES) Flow Rate: 9L/min. 3 Star rating WELS registration #SM13614