SMART PRINTER MODULE

Ref. 026919



The SPM module is a thermal printer compatible with GYSFLASH CNT chargers. Ideal for traceability, this ultra-compact module allows you to print a summary of the charging cycle in ticket. It can be powered directly by the charger via its SMC connection cable or by a power cord to increase its printing speed. The printer can be mounted with its magnetic base in a vertical or horizontal position.



Thermal printing, no ink or toner is required.

Ultra-compact format,

optimizes workshop space.


Built-in protections:



Thermal failure Tray empty

2 power supply modes:

Powered by the network = fast printing speed





Power supply network

High speed

SMC connection system (communication network)

Normal speed

USB 2.0 connectivity,

2 ports to connect a 1D/2D barcode reader and keyboard.

Magnetic support, to be fixed on a workstation or trolley. Printing possible in all positions.

Technical specifications:

• resolution: 200 dpi

• printing speed: max. 80 mm/s

• paper width: 57 mm



Battery Charger Unit GYSFLASH 101.12 CNT

SN: 00.00.000000.000000 Date: 06/01/2019 01:47 Charge number: 457

Vehicle data

Customer: M. Smith Model: Golf 4 VIN: 65SG4654D4DGH654G Number plate: HJ-456-GH

Battery data

Model: Varta Number: 56789 Rated voltage: 12V Rated capacity: 67Ah Type: Lead-acid

Charge data

Type: Pb-CHARGE Profile: AGM Selected voltage: 12V Selected capacity: 67Ah

Initial battery status

Initial voltage: 12.4 V Initial status: CHARGED

Charging information

Charging process: 1009 Charge duration: 00:04:10 Injected Ah: 0.0Ah

Final battery status

Charging voltage: 14.7V Final voltage: 13.5V Final status: CHARGED



Includes:

- SMC connection cable (DB9)
- IEC C13 power cord
- 1 paper reel

ACCESSORIES (OPTIONS)



Paper reel 57 mm 056633



Mini keyboard AZERTY 027725 QWERTY 027770







Single trolley GYSFLASH XL 027749

- → 50/60 Hz	I
100-240 V AC	140 - 90 m



included x1



2.0



1.35



140 x 105 x 133



TP 21



50 cm