MULTIWELD 250T

WELDING MACHINE MMA / MIG-MAG INVERTER (40 ≥ 250A)

Ref. 063518



The MULTIWELD 250T is a semi-automatic three-phase welding machine, combining MIG/MAG, cored wire and MMA welding processes. Its intuitive interface integrates digital displays for easy and precise adjustment. Recommended for welding steel, stainless steel and aluminium, the MULTIWELD 250T is perfect for light fabrication and maintenance workshops.

MULTIPROCESS

- MIG/MAG welding:
- steel wire and stainless steel: Ø 0.6 to 1.2 mm
- aluminium wire and cored wire (polarity reversal): Ø 0.9 to 1.2 mm
- **MMA welding:** basic and rutile electrodes (up to \emptyset 5 mm).

OPTIMISED MIG/MAG SETTINGS

- Choice of the trigger mode: 2T or 4T.
- **Welding guide:** tables on the front panel assist the user to adjust and fine tune the voltage and the diameter of the filler wire according to the thickness of material being welded.

INTUITIVE

- **Display readable** even in bright light.
- **Simple user interface** with ergonomic controls allowing gloved use.

INTEGRATED WIRE FEEDER

- Compatible wire reels: Ø 200 / 300 mm
- Wire feeder with 2 rollers.
- EURO torch connector for quick assembly/disassembly.


PRE-HEATING, PURE CO2

- Pre-installed socket (36 V 4.2 A) for gas heater in pure CO2 welding (heater not included).
- Compatible with US (type A) and EURO electrical sockets (type C/E/F).

STURDY

- Reinforced structure.
- Reinforced wheels for better stability and movement
- Support for gas cylinder up to 4 m³.






ACCESSORIES (option)





Earth clamp 250 A - 4 m - 25 mm² 043794







	30 l/min
	041622
(E)	041219
	041646

•	[AM]	I ₂ MMA	I ₂ MIG	⊕ ‡	ømm	⊕ ‡ ømm		V Ø mm	©	ф	équipé d'origine / original equipement / originalausstatung / equipamiento de fabrica	EN 60974-1 (40°C)	U _o	1	<u> </u>	IP	Protected & compatible
50/60 Hz	Α	A	A	GAS	NO GAS	200	300	Ø mm	Electronic Control	m/min	③	X (40°C)	٧	cm	kg		power generator (+/-15 %)
400V 3~	16	40 → 250	40 → 250	0.6 - 1.2	0.9 - 1.2	✓	~	1.6 → 5	-	2.0 - 15.0	0.8 1.0	200A @ 60% 180A @ 100%	59	77 x 79 x 47	40	IP 21	10 kVA