

GYSMATIC GOGGLE 3 TRUE COLOR



REF. 068704

The GYSMATIC GOGGLE 3 welding helmet is a blend of cutting-edge technologies for exceptional user comfort. Its field of vision is up to eight times wider thanks to its deeper-cut nose bridge and two side windows. Panoramic viewing allows you to see potential peripheral dangers such as beams and obstacles. The mask's premium filter gives the welder realistic colour vision.

FEATURES

- Revolutionary design with an extended field of vision.
- Fully adjustable Ergofit+ headband. Perfectly balanced for an outstanding level of comfort.
- Shade level: 3.
- Extra-wide panoramic field of vision.
- Control panel with digital display.
- Smart mask with automatic setting adjustments according to the working conditions including light and operating mode, etc.
- Seven highly sensitive sensors provide maximum efficiency.
- It's TrueColor-technology filter delivers a more realistic and detailed colour reproduction than conventional filter systems.



Classic
★

TrueColor
★★★★

TECHNICAL INFO

UV/IR protection	DIN 15
Classification	1/1/1/1
Clear shade	3
Dark shades	Main lens : 4 >8 - 8 >13 Side windows : 10
Reaction time	0,1 ms
Delay time (back to shade 4)	0,06 > 1 sec
Power Supply	solar powered & two batteries (CR2032)
Weight	573 g
Adjustable settings	Manual / Automatic
	Light sensitivity, delay, shade level, welding, grinding
	Side-window light sensitivity
Light sensor	Gradual return to clear state
	7
Applications	MMA 5 ▶ 400 / TIG 2 ▶ 300 / MIG-MAG 5 ▶ 400
Standards	CE / EN 175B / EN 166 / EN 379



Comes with an Ergofit+ headband



- 1 SHADE : Tint adjustment (4>8 / 8>13)
- 2 SETTINGS: Light-sensitivity setting (1>8)
- 3 DELAY : Set the time to return to clear state
- 4 Adjusting the side window's light sensitivity

■ Automatic or Manual settings.

■ Comfort feature «GRADUAL» return to clear state

OPTIONS

Welding-helmet protective drawstring bag
043299



Welding-helmet protective backpack
066656



Anti-perspiration headband x2
043466



Spare lenses



385.8x137.7 (x10) 070998



60.5x53.2 (x10) 071001