



ELECTROMIG 300 SYNERGIC



Overview

ELECTROMIG 300 SYNERGIC

cod. 816065

MIG-MAG/FLUX/BRAZING/MMA and TIG DC-Lift multiprocess inverter welding machine controlled by a microprocessor, with 4-roller wire feeder.

Flexible use with various welded materials (steel, stainless steel, aluminium) or brazed materials (galvanised sheet metal). Wide variety of application fields, from industry to maintenance, installation to bodywork activities.

Synergic adjustment makes the product simple to use.

The Made in Telwin ATC technology makes it easy to achieve excellent standards of welding on thin materials thanks to state-of-the-art control of the arc.

Features:

- Manual or synergic operating;
- 30 pre-set synergic curves;
- MIG-MAG adjustments: wire up slope, electronic reactance, wire burn-back time, post gas;
- 2/4 time operation selection, spot, inch and mm material thicknesses;
- Protections: thermostatic, overvoltage, undervoltage, overcurrent, engine driven generator (+/-15%);
- TIG Lift

Complete with MIG-MAG torch, cable and earth clamp.



MMA TIG DC LIFT



COIL 15 kg



EAC CERTIFICATION



MIG-MAG FLUX



CE MARKING

Technical data



CODE 816065



MAX ABSORBED CURRENT 15 A



D. USABLE ELECTRODES IN DC 1,6 - 6 mm



THREE PHASE MAINS VOLTAGE 400 V



ABSORBED CURRENT AT 60% - MAX 10 A



STEEL WELDING WIRE DIAMETER 0,6 - 1,2 mm



ELECTROMIG 300 SYNERGIC

F	MAINS FREQUENCY 50 / 60 Hz	P _{MAX}	MAX ABSORBED POWER 9 kW	SS	INOX WELDING WIRE DIAMETER 0,8 - 1,2 mm
A _{MIN MAX DC}	CURRENT RANGE 20 - 300 A	P _{60%}	ABSORBED POWER AT 60% 6,5 kW	AL	ALUMINIUM WELDING WIRE DIAM. 0,8 - 1,2 mm
A _{MAX 40°C DC}	MAX CURRENT DC (EN 60974-1) 270 @ 30% A	η	EFFICIENCY 90 V	FX	FLUX CORED WELDING WIRE DIAM. 0,8 - 1,2 mm
A _{60% 40°C DC}	DC CURRENT 205 A	φ	POWER FACTOR (cosphi) 0,9	BZ	BRAZING WIRE DIAM. 0,8 - 1,2 mm
V _{0 DC}	MAX NO LOAD VOLTAGE 63 V				

Included Accessories

TORCH HOOK - 645704

CABLE 25MMQ 3M-WORK CLAMP-ATLAS 50MMQ - 713192

MT25 MIG TORCH 3M - 742183

FEED ROLL 4R 0,6FE-0,8/0,9FE "P-K" - 742576