

# Magnetic Door Lock Double (1200) x 2

## Features:

Collinear Load Test 500kgx2 / 1200lbsx2  
Dual Voltage 12 or 24V DC (optional)  
The Standard Voltage is 12V DC when Finished  
MOV Provides Reverse Current Protection  
LED Indicator and Contact Switch  
Anti-Residual Magnetism Designed  
High Strength Material, Anodized Aluminum Housing  
Design without Mechanical Failure  
Increase the holding Force, Dual Insulative Housing  
CE Certificate

## Specifications:

Size: 530Lx72Wx40H(mm) / 20.87Lx2.83Wx1.57H(in)  
Armature Plate Dimension: 185Lx60Wx13H(mm) / 7.28Lx2.36Wx0.51H(in)  
Holding Force: 500kgx2 / 1100Lbsx2  
Input Voltage: 12 or 24VDC  
Current Draw: 12V/500mA<sub>x2</sub> or 24V/250mA<sub>x2</sub>  
Surface Temp: Less than  $\leq 20^{\circ}\text{C}$  (68°F)  
Operating Temp: -10-+55°C(14-131°F)  
Humidity: 0-90%(non-condensing)  
Cover Finish: Anodized aluminum  
Lock Finish: Zinc  
Armature Plate Finish: Zinc  
Weight: 9KG / 19.84lb



