

ALPINE



Silverash

Wheat

Sienna

DESCRIPTION

| | | | |
|---------------------------|--------|----|------------------------------------|
| Luxury Vinyl Plank | EN 649 | – | Heterogeneous PVC |
| Plank Size 1 | EN 427 | mm | 177.8x1219.2 |
| Total Thickness | EN 428 | mm | 3.0 |
| Planks / Meterage per box | – | – | 15 Planks, 3.26m ² /box |
| Plank Size 2 | EN 427 | mm | 228.6 x 1524 |
| Total Thickness | EN 428 | mm | 5.0 |
| Planks / Meterage per box | – | – | 8 Planks, 2.79 m ² /box |
| Wear Layer | EN 429 | mm | 0.55 (±0.05) |
| Surface Treatment | – | – | PU / Nano silver coating |

CLASSIFICATION

| | | | |
|-------------------------|-----------------|------------|--------------------------|
| Classification | EN 685 | class | 33–42 |
| Fire Classification | EN 13501-1 | class | Bfl-S1 |
| | BCA SPEC C110-3 | – | Complies |
| Slip Resistance | DIN 51130 | class | R10 |
| | AS 4586 | Appendix D | R10 |
| | EN 13893 | class | DS |
| Electrical Conductivity | EN 1815 | – | ≤ 2kV |
| | EN 1081 | – | ca. 10 ¹¹ Ohm |
| Residual Indentation | EN 433 | mm | <0.1 |

PERFORMANCE

| | | | |
|----------------|-------------|-------|-------------|
| Castor Chair | EN 425 | – | Yes, Type W |
| Colourfastness | ISO 105 B02 | grade | m>6 |

ENVIRONMENTAL

| | | | |
|--|-------------------|-----------|------------------------------|
| Floor Heating | – | celcius | Yes, max. 27° |
| Environmental | Floor Score | – | Indoor Air Quality Certified |
| | (SCS-EC10.2-2007) | | Low VOC emissions |
| Volatile Organic Compounds (VOC) Emission Factor | eco Institut | class | Low VOC, Class A+ |
| | (ISO/IEC 17025) | | |
| Quality Control Management | ISO 9001 : 2000 | certified | |
| Environmental Management | ISO 14001 : 2004 | certified | |



Specifications are subject to manufacturing tolerances and may be changed without notice. Colour variation may occur between sample and supplied products due to dye lot tolerances.