

AQUA-TUF

PRODUCT SPECIFICATIONS

Type	Hybrid	Style	Single Plank LVT
Board Construction	0.3mm virgin PVC wear layer, 5mm core limestone / PVC wood / bamboo dust composite		
Description	Wood Plastic Composite Single Plank	Dimensions	1760 x 190 x 8mm
Boards per Pack	6	m² per Pack	2.006m ²
Pack Weight	16.84kg	m² per Pallet	160.48m ²
Installation Method	Floating	Finish	Extra Matt Finish
Coating	Gloss level 8 - 10%	Profile	4 Sided Micro-bevel
Underlay	1.5mm high density closed cell foam attached		

TEST DATA

Fire Rating	Critical Heat Flux: 6.5kW/m ² Smoke Value: 127% minute	Thickness Swell	Class 4 Heavy Commercial
Slip Resistance	P3	Stain Resistance	Class 4 Heavy Commercial
Load Test	0.02mm at 250 PSI	Impact Resistance	Class 4 Heavy Commercial
Emissions Test	No Disclosed Formaldehyde - E0	Colour Resistance to light	Class 4 Heavy Commercial
Acoustic Test	FIIC / 53db	Underfloor Heating	Suitable to a maximum of 27°
Thermal Resistance	0.57 (R Value)	Castor Chair Suitability	Class 3 Commercial
Floor Score Certification	Floor Score Certified		

Warranty	25 Year Residential Warranty 10 Year Commercial Warranty
Moisture resistance	Lifetime waterproof warranty