

HARDWOOD + MATT BRUSHED

PRODUCT SPECIFICATIONS

Туре	Australian Timber	Style		Single Plank	
Description	Engineered multi-layer natural timber veneer interlocking floor boards featuring G5 Locking System				
Board Construction	3mm hardwood face layer 10mm Poplar base	Profile		Micro-Bevel	
Installation Method	Direct Stick or Floating	Finish		Matt Brushed <8%	
Coating	Factory coated with seven layers of UV cured acrylic	Underlay		Standard – 2mm Closed Cell Foam Acoustic – 3mm or 5mm ImpactaMat	
Dimensions	1820/2100 x 136 x 14mm		1820/2100 x 180 x 14mm		
Boards per Pack	8		6		
m² per Pack	1.980m²/2.284m²		1.966m²/2.268m²		
m² per Pallet	126.720m²/146.176m²		129.756m²/149.688m²		
Pack Weight	23kg		23kg		

TEST DATA

Fire Rating	Critical Heat Flux: 4.2kW/m² Smoke Value: 8% minute	Slip Resistance	P3
Janka Rating	6 - 11		

Warranty	25 Year Residential Warranty 10 Year Commercial Warranty	
Variations in Timber	Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species.	
	Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour.	