

HARDWOOD + RUSTIC

PRODUCT SPECIFICATIONS

Type	Australian Timber	Style	Single Plank
Description	Engineered multi-layer natural timber veneer interlocking floor boards featuring G5 Locking System		
Board Construction	3mm hardwood face layer 10mm Poplar base	Profile	Micro-Bevel
Installation Method	Direct Stick or Floating	Finish	Matte Smooth
Coating	Factory coated with seven layers of UV cured acrylic	Underlay	Standard – 2mm Closed Cell Foam Acoustic – 3mm or 5mm ImpactaMat
Dimensions	1820/2100 x 136 x 14mm	1820/2100 x 180 x 14mm	
Boards per Pack	8	6	
m² per Pack	1.980m²/2.284m²	1.966m²/2.268m²	
m² per Pallet	126.720m²/146.176m²	129.756m²/149.688m²	
Pack Weight	23kg	23kg	

TEST DATA

Fire Rating	Critical Heat Flux: 4.2kW/m² Smoke Value: 8% minute	Slip Resistance	P3
Janka Rating	6 - 11		

Warranty	25 Year Residential Warranty   10 Year Commercial Warranty
Variations in Timber	<p>Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species.</p> <p>Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour.</p>