

## LUXURY OAK

### PRODUCT SPECIFICATIONS

<b>Type</b>	European Oak	<b>Style</b>	Single Plank
<b>Description</b>	Engineered multi-layer natural timber veneer interlocking floor boards featuring G5 Locking System		
<b>Board Construction</b>	3mm hardwood face layer 11mm thick plywood mixed with Poplar and Eucalyptus (bottom layer is Poplar)		
<b>Installation Method</b>	Direct Stick or Floating	<b>Finish</b>	Light Wire Brush
<b>Coating</b>	7 Coats of Treffert Lacquer combined with wire brush and colour stain, 4 Base Coats, 1 Coat of Abrasive Resistance Coating and 2 Coats of Top Coat		
<b>Profile</b>	0.6mm Bevel on two sides and square on end join	<b>Underlay</b>	Standard - 2mm Closed Cell Foam Acoustic - 3mm or 5mm ImpactaMat
<b>Dimensions</b>	1860 x 189 x 14mm	<b>Boards per Pack</b>	8
<b>m<sup>2</sup> per Pack</b>	2.812m <sup>2</sup>	<b>m<sup>2</sup> per Pallet</b>	112.48m <sup>2</sup>
<b>Pack Weight</b>	25.3kg	<b>Timber Grade</b>	ABCD

### TEST DATA

<b>Fire Rating</b>	Critical Heat Flux: 4.2kW/m <sup>2</sup> Smoke Value: 8% minute	<b>Slip Resistance</b>	P2
<b>Janka Rating</b>	6	<b>Certification</b>	Forestry Stewardship Certification (FSC)

<b>Warranty</b>	25 Year Residential Warranty   10 Year Commercial Warranty
<b>Variations in Timber</b>	<p>Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species.</p> <p>Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour.</p>