### embelton.com

## EMBELTON



## Luxury Oak Herringbone

Our timber Herringbone range provides the beauty and prestige of European Oak while bringing an added touch of luxury to your home. Herringbone flooring stands out as a remarkably versatile choice, offering a range of stylistic possibilities for home interiors. Particularly effective in hallways and entranceways, herringbone flooring creates a striking initial impression of your residence, guiding visitors through the space with its distinctive pattern.

# 9 Layers of UV Acrylic Coating 3mm Veneer of Engineered Oak Timber 11mm Engineered Multiply Substrate T&G Joining System

### PRODUCT SPECIFICATIONS

Туре	European Oak	Board Dimensions	600 x 120 x 14mm	
Description	Engineered multi-layer natural timber veneer interlocking floor boards featuring Tongue & Groove Joining System			
Installation Method	Direct Stick	Profile	Micro-Bevel	
Coating	Factory Coated with Nine Layers of UV Cured Acrylic	Finish	Light Wire Brush	
Timber Grade	ABCD			

### PACK SPECIFICATIONS

M <sup>2</sup> Per Pack / Pallet	2.81m²/112.48m²	Boards Per Pack	16 (8 left / 8 right)
Pack Dimensions	615 x 248 x 120mm	Pack Weight	12kg

#### TEST DATA & WARRANTY

Fire Rating	Critical Heat Flux: 3.3kW/m2 Smoke Value: 29% minute	Slip Resistance	P3
Acoustic Rating	58 LnTw*	Sustainability	Forestry Stewardship Certification® (FSC®)
Warranty	25 Year Residential Warranty   10 Year Commercial Warranty		

Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species. Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour. Access complete warranty information at <u>embelton.com</u>



The mark of responsible forestry FSC\* C132800