

## LUXURY OAK XL

## PRODUCT SPECIFICATIONS

Туре	European Oak	Style	Single Plank	
Description	Engineered multi-layer natural timber veneer interlocking floor boards featuring Tongue & Groove Locking System			
<b>Board Construction</b>	4mm hardwood face layer 11mm thick plywood mixed with Poplar and Eucalyptus (bottom layer is Poplar)			
Installation Method	Direct Stick	Finish	Light Wire Brush	
Coating	7 Coats of Treffert Lacquer combined with wire brush and colour stain, 4 Base Coats, 1 Coat of Abrasive Resistance Coating and 2 Coats of Top Coat			
Profile	Micro-Bevel	Timber Grade	ABCD	
Dimensions	2200 x 220 x 15/4mm	Boards per Pack	5	
m² per Pack	2.42m <sup>2</sup>	m² per Pallet	89.600m <sup>2</sup>	
Pack Weight	24kg			

## TEST DATA

Fire Rating	Critical Heat Flux: 4.2kW/m² Smoke Value: 8% minute	Slip Resistance	P3
Certification	Forestry Stewardship Certification (FSC)		

Warranty	25 Year Residential Warranty   10 Year Commercial Warranty	
Variations in Timber	Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species.	
	Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour.	
	Single plank for engineered flooring may include some nested lengths. All orders to be dispatched to the nearest full pack.	